



ENGINEERING & TECHNICAL DATA — Flexadux® PV R-3

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
1.25	.3	.035	1.4	2:1	29	30
1.5	.36	.035	1.5	2:1	29	30
2	.46	.035	2.42	2:1	29	30
2.5	.54	.035	2.84	2:1	29	30
3	.65	.035	3.25	2:1	29	20
3.5	.73	.035	3.51	2:1	29	20
4	.91	.045	4.42	2:1	29	20
5	1.13	.045	5.53	2:1	16	17
6	1.36	.045	6.63	2:1	8	15
7	1.58	.045	7.17	2:1	5	13
8	1.8	.045	7.7	2:1	3	11
10	2	.045	9.92	2.5:1	3	8
12	2.4	.045	12	2.5:1	2	7
14*	2.9	.045	14	2.5:1	1.27	6
16*	3.3	.045	16	2.5:1	.7	5

*Wire not coated

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Heavy weight PVC hose reinforced with a coated spring steel wire helix (sizes 14" I.D. & above not available with a coated wire)

Temperature Range: 20°F to 160°F

Standard Color: Blue and Clear

Standard Lengths: 25 & 50 Feet

- Blue is listed as UL 94V-0 flame retardant

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE

info@jmesales.com E-MAIL
www.JMESales.com WEB