



ACCESS HOSE INTERNATIONAL

QUALITY HOSE. TRUSTED SOLUTIONS.

DOUBLE JACKET — MILL HOSE —

PRODUCT DESCRIPTION

Access Hose International Double Jacket Mill Hose is a heavy duty lay-flat hose engineered for maximum durability and performance in the toughest environments. Constructed with a natural rubber liner and a thicker double jacket, this hose delivers superior abrasion, puncture, and cut resistance for demanding applications.



FEATURES & BENEFITS

- ✓ Heavy duty lay-flat hose with thicker double outer jacket
- ✓ Extra outer jacket provides higher abrasion, puncture, and cut resistance
- ✓ Extra thicker cover makes the hose ideal for rugged and tough conditions
- ✓ Temperature range from -22°F to 158°F (-30°C to 70°C)
- ✓ Aluminum and brass couplings and others available on request
- ✓ Other diameters available
- ✓ Different lengths including 50', 75', 100' etc. on request
- ✓ Main applications include water discharge, wash down, and industrial fire fighting

CONSTRUCTION

JACKET:	Synthetic blend compound (double jacket)
REINFORCEMENT:	High tenacity polyester yarn
WEAVE:	Twill weave
LINING:	Natural rubber
COUPLINGS:	Aluminum (standard) Brass or other options available upon request

APPLICATIONS



Water
Discharge



Wash
Down



Industrial
Applications



Fire
Fighting

AVAILABLE SIZES & PERFORMANCE (250 PSI WORKING PRESSURE)

NOMINAL SIZE	HOSE I.D.		WORKING PRESSURE 250 PSI (17 BAR)		BURST PRESSURE 750 PSI (52 BAR)		APPROX. WEIGHT (DOUBLE JACKET)	
	in.	mm	PSI	BAR	PSI	BAR	lbs/ft	kg/m
1"	1.00	25	250	17	750	52	0.28	0.42
1-1/2"	1.50	38	250	17	750	52	0.40	0.60
2"	2.00	52	250	17	750	52	0.55	0.82
2-1/2"	2.50	65	250	17	750	52	0.67	1.00
3"	3.00	75	250	17	750	52	0.82	1.22
4"	4.00	102	250	17	750	52	1.10	1.64

Weights are approximate and may vary.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE

info@jmesales.com E-MAIL
www.jmesales.com WEB