

PRODUCT DESCRIPTION

Access Hose International Single Jacket Mill Hose is a heavy duty lay-flat hose engineered for maximum durability and performance in the toughest environments. Constructed with a natural rubber liner and a single jacket, this hose delivers excellent abrasion, puncture, and cut resistance for demanding applications.



FEATURES & BENEFITS

- ✓ Heavy duty lay-flat hose with single jacket construction
- ✓ Excellent abrasion, puncture, and cut resistance
- ✓ Lightweight and flexible for easy handling and storage
- ✓ Temperature range from -22°F to 158°F (-30°C to 70°C)
- ✓ Aluminum and brass couplings and others available on request
- ✓ Other diameters available
- ✓ Different lengths including 50', 75', 100' etc. on request
- ✓ Main applications include water discharge, wash down, and industrial applications

CONSTRUCTION

JACKET:	High tenacity polyester yarn
WEAVE:	Twill weave
LINING:	Natural rubber
COUPLINGS:	Aluminum (standard) Brass or other options available upon request

APPLICATIONS



Water
Discharge



Wash
Down



Industrial
Applications



Construction
Sites

AVAILABLE SIZES & PERFORMANCE (150 PSI WORKING PRESSURE)

NOMINAL SIZE	HOSE I.D.		WORKING PRESSURE 150 PSI (10 BAR)		BURST PRESSURE 450 PSI (30 BAR)		APPROX. WEIGHT (SINGLE JACKET)	
	in.	mm	PSI	BAR	PSI	BAR	lbs/ft	kg/m
1"	1.00	25	150	10	450	30	0.20	0.30
1-1/2"	1.50	38	150	10	450	30	0.28	0.42
2"	2.00	52	150	10	450	30	0.35	0.52
2-1/2"	2.50	65	150	10	450	30	0.45	0.67
3"	3.00	75	150	10	450	30	0.55	0.82
4"	4.00	102	150	10	450	30	0.80	1.19

Weights are approximate and may vary.