

# Double Wall Tank Packages



## GAIN FULL CONTROL OVER YOUR OIL MANAGEMENT AND MOVE TOWARD GENUINE OIL INDEPENDENCE!

Discover Introducing the new Alemite double wall tank package—your path to oil independence and the ultimate solution for on-site fluid storage and dispensing. Ships fully assembled and UL/EPA compliant, it safely handles motor oil, gear oil, hydraulic fluids, ATF, and heating oil. Lightweight, durable design, it offers compact, cost-effective performance and maximum protection for your operations.

### FEATURES AND BENEFITS:

- Allows you to be oil independent
- Ships fully assembled
- Double wall tanks meet the UL SU2258 standards.
- Complaint with the EPA's SPCC regulations.
- Store and dispense fluids such as motor oil, gear oil and heating oil, hydraulic fluids, and ATF.
- Comes installed with Alemite's staple 9968 RAM pump, 8078 heavy duty reel and 3670 electronic meter.
- Installation is fast and easy. Simply connect to compressed/shop air and our 7936-air filter/regulator will regulate safe and proper PSI (max 150).
- Outer tank layer acts as secondary containment and it can hold 110% of the inner tank fluids for maximum protection.
- Four 2" ports and includes tank gauge, lockable fill cap & emergency vent.
- Compact and economical.
- Up to 50% lighter than conventional steel tanks.
- Wide handles are positioned on the front of the tank to allow for easy handling and transport when empty



Part Number	Tank Size
ALM165DWTP-V1	165 gallons
ALM275DWTP-V1	275 gallons
ALM400DWTP-V1	400 gallons

# Double Wall Tank Packages



Achieve oil independence with the Alemite double wall tank package, featuring four key components: the 3670 electronic fluid meter, 7936 filter regulator, 8078-D heavy duty oil reel (50 ft., 1/2" ID), and 9968 stationary RAM Pump. This reliable system ensures efficient fluid management and greater control over your oil resources. Alemite double wall packages can be ordered through your Lincoln Industrial account.

## Alemite 9968

stationary RAM Pump

- Handles fluids up to SAE 140
- Meets OSHA noise requirements (85 dB)
- 3" (76 mm) diameter air motor
- Will mount to 1 1/2" (38 mm) suction pipe from remote tank
- Easy serviceability
- 1/4" (6 mm) air inlet



## Alemite 3670

electronic fluid meter

- Electronic digital readout
- Stainless steel tip
- Ergonomic trigger design for easy dispensing
- Rubber guard to protect meter from damage
- Measures in pints, quarts, gallons or liters
- Uses 2 standard AAA batteries (not included), replaceable with a coin screw on back of meter



## Alemite 8078-D

heavy duty oil reel, 50ft. 1/2" ID

- Anti-lockout design – Ratchet prevents lockup when hose is fully extended, eliminating the need for manual release of the paw
- Swivel and reel ball bearings reduce torque load on power spring for smooth retraction every time
- Sealed bearings prevent contamination and minimize maintenance, a critical performance factor in dirty environments
- Max Pressure 1500 PSI



## Alemite 7936

filter regulator

- Max Inlet Pressure: 150 psi (10 bar)
- Inlet/Outlet: 1/4" NPTF(f)
- Operating Temperature: 32-125°F (0-52 °C)



Alemite is an SKF Group Brand

167 Roweland Drive  
Johnson City, TN 37601  
Toll Free U.S.: 866-4-ALEMITE (866-425-3648)  
Toll Free Canada: 800-267-8022  
International: 803-802-0001  
[www.alemite.com](http://www.alemite.com)

Pub # LIT224- EMXXX

