Used Fluid Equipment Truck Drain and Drain-Pit Boss



The truck drain comes pre-assembled allowing for immediate use. Includes "used oil only" and "used anti-freeze only" decals for fluid identification. Connects to a used oil evacuation system using a cam-lock kit and evacuation system.

The Pit Boss rolling pit drain captures used fluids. Specifically designed to easily roll on guide tracks in the user's pit and connect to a used fluid evacuation system.

The low volume truck drain comes pre-assembled allowing for immediate use. Connects to a used oil evacuation system using a 3/4" cam-lock kit for anti-freeze or a 1" cam-lock kit for used fluid.



Features

Truck Drain

- Two fixed 8" wheels and one swivel caster
- Double baffles with upper screen and a catch lip help prevent fluid from splashing out
- Tubular U-handle design for excellent maneuvering
- All steel design

Low Profile Truck Drain

 Two anti-splash baffles, side splash guards and a metal catch screen. Select a 3/4" cam-lock kit for anti-freeze or a 1" cam-lock kit for used fluid

Pit Boss

- Two anti-splash baffles, side splash guards and a metal catch screen
- Front and rear drain ports
- 3" diameter wheels which are mounted to accommodate a pit track width of 34" to 53"
- Tool shelf below the tank for pit service tool
- All steel design

TECHNICAL DATA				
MODELS	4120-003 4120-004	4120-006	4140-060 4140-020	
Tank Capacity	5.2 gal (20 l)	26 gal (98.4 l)	34 gal (128.7 l)	
Fluid Outlet	4120-003 3/4" for anti-freeze 4120-004 1" for used oil	1"	4140-060 1" cam-lock nipple 4140-020 1" NPT(F) bare	
Measurements	9" H x 15" W x 32" L	9" H x 24" W x 36" L	16.72" H x 28.4" W x 34" L, 2" adjustable unit height	
Wetted Materials	Zinc Plated Steel, Steel, Viton*, HDPE, and PVC	Zinc Plated Steel, Steel, Viton [°] , HDPE, and PVC	Zinc Plated Steel, Steel, Viton*, HDPE, and PVC	
Service Bulletin	SB 4234	SB 4051	SB 4227	

MODELS Available	DESCRIPTION	
4120-003	Low Profile Truck Drain for anti-freeze	
4120-004	Low Profile Truck Drain for oil	
4120-006	Low Profile Truck Drain Bare	
4140-060	Drain - Pit Boss with Quick Connect Kit 4140-061	
4140-020	Drain - Pit Boss Bare	

Warning! Not to be used with flammable fluids.

CAM-LOCK COUPLER & NIPPLE RATED For 250 PSI (17 BAR)			
Cam-Lock Coupler & Nipple		4140-044 Coupler 3/4" NPT(F)	
		4140-017 Coupler 1" NPT(F)	
		4140-054 Nipple 3/4" NPT(F)	
		4140-055 Nipple 1" NPT(F)	
		4140-045 Nipple 3/4" NPT(M)	
		4140-018 Nipple 1" NPT(M)	
		4140-046 Dust Cap 3/4" NPT(F)	
		4140-019 Dust Cap 1" NPT(F)	
	111	4140-052 Dust Plug 3/4" NPT(M)	
		4140-053 Dust Plug 1" NPT(M)	

CAM-LOCK COUPLER & NIPPLE RATED FOR VACUUM OR UP TO 3,000 PSI (207 BAR) 4140-061 Cam-Lock Kit 1" for used oil for use with Pit Boss Bare 4140-020 Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple 4140-067 Cam-Lock Kit 3/4" for anti-freeze for use with Pit Boss Bare 4140-020 Includes: Fluid Ball Valve, Cam-Lock nipple, Cap, and Hex nipple Hose Kit for used oil evacuation Includes: 4140-017 - Cam-lock coupler 1", 8181-002X - Hose low pressure 2.5" x 1"