The Bosworth Company

Sea-Lect® Check Valve

CV-2600A/2600B

CV-2600A - Aluminum

- **Creates & maintains pump prime**
- **Doubles pump lift for Guzzler "2600" Series pumps**
- **Prevents fluid backflow**
- **Available in either aluminum or bronze**
- **Accommodates 1-1/4" - 2" hose**

Performance

Max Pressure	20 psi (1.4 kg/cm^2)
Max Lift/Head	46 ft (14 m)
Pressure Drop (Cracking Pressure)	2.7 x 10^{-2} psi (0.75 in. of water) 1.9 x 10^{-3} kg/cm^2)
Max Service Temp	190°F (88°C)

Available Ports

in	1-1/4	1-1/2	2
cm	3.18	3.81	5.08
Hose (Smooth)			**S**
NPT Female (Tapped)	•		
NPT Male (Threaded)		•	

S Standard • Optional



CV-2600B - Bronze

Valve Options

Flapper — Steel plate reinforced. General purpose liquid transfer.

Materials

Body *	Epoxy-coated Aluminum / Blue Bronze / Bronze
Valve *	Flapper: Buna-N
Fasteners	Stainless Steel

** In contact with fluid*



	in	cm
A	5-3/4	14.6
B	3	7.6
C	4	10.2
Weight	1.15 lb	0.52 kg

JME® ELLSWORTH
A John M. Ellsworth Company
John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800·333·3331 PHONE

info@jmesales.com E-MAIL
www.JMEsales.com WEB

Sea-Lect® Check Valve
CV-2600A / 2600B

Example: CV-2600A-1-9090

- Sea-Lect Check Valve
- Model style 2600A (Aluminum/Blue)
- Flapper Valve
- 2” Smooth Hose Connections

CV – 2600A – 1 – 90 90

Sea-Lect Product

Option	Code
Check Valve	CV

Family

Option	Code
2” Nominal Port Size, Aluminum	2600A
2” Nominal Port Size, Bronze	2600B

Valve

Option	Code
Flapper (Buna-N)	1

Hose Connections

Option	Code	
	Inlet	Outlet
1-1/4” NPT Tapped	71	71
1-1/2” NPT Threaded	82	82
2” Smooth	90	90