



MATERIAL DESCRIPTION

MODEL	QTY.	HORIZONTAL DW FIREGUARD SKID TANK
INNER DIAMETER		5'-4"
OUTER DIAMETER		5'-11"
INNER LENGTH		9'-0"
OUTER LENGTH		9'-8"
CAPACITY		1500 GAL. NOMINAL
INNER GAUGE		7ga.
OUTER GAUGE		7ga.
CODE		UL 2085
SUPPORTS	A 2	FULL BOX SKIDS
FILL	B 1	4" #150 FULL COUPLING
LEVEL GAUGE	C 1	2" #150 FULL COUPLING
SECONDARY E-VENT	D 1	6" SCH 40 PIPE NIPPLE TOE (OUTER E-VENT)
PRIMARY E-VENT	E 1	6" SCH 40 PIPE NIPPLE TOE (INNER E-VENT)
WORKING VENT	F 1	2" #150 FULL COUPLING
SUPPLY	G 1	2" #150 FULL COUPLING
MONITOR	H 1	2" MONITOR PIPE w/ 2" FULL COUPLING
DECALS	I 1	STI FIREGUARD DECAL KIT
LIFT LUG	J 2	SMALL LIFT LUG (PHOENIX TYPE)
GROUND LUG	K 2	1/4"x2"x2" Angle Clip w/1/2"φ
REMOTE LEVEL GAUGE	L 1	2" #150 FULL COUPLING
	M	
POUR PORTS	N 2	POUR PORTS 2" WELD FLANGES w/PLUGS

TANK SHALL BE BUILT & LABELED PER UL 2085, STI FIREGUARD
UL FILE # MH21280

Surface Prep: Brush Blast
Paint: Polane White
Testing: Per STI Fireguard
Operating Pressure: Atmospheric
Estimated Dry Weight: 6,200lbs