



SCALE

MATERIAL DESCRIPTION

| MODEL | KEY | QTY | HORIZONTAL SW UL 142 SKID TANK |
|--------------------|-----|-----|-----------------------------------|
| Tank Diameter | | | 5'-4" |
| Tank Length | | | 6'-0" |
| Capacity | | | 1,000 US Gallons Nominal |
| Tank Gauge | | | 10 Gauge |
| Code | | | UL 142 |
| Supports | A | 2 | Skids Full Length - 10 Gauge |
| Fill Opening | B | 1 | 2" 150# Weld Flange W/Plastic Cap |
| Pump Opening | C | 1 | 2" 150# Weld Flange W/Plastic Cap |
| Gauge Opening | D | 1 | 2" 150# Weld Flange W/Plastic Cap |
| Op Vent Opening | E | 1 | 2" 150# Weld Flange W/Plastic Cap |
| Tank E-Vent | G | 1 | 6" Sch 40 Pipe Nipple (TOE) |
| Remote Level Gauge | I | 1 | 2" 150# Weld Flange W/Plastic Cap |
| Lift Lug | J | 2 | Small Lift Lug |
| Tank Drain | K | 1 | 1" 150# Weld Flange |
| UL Labeling | L | Set | Labeled Per Section 48 UL142 Code |

TANK SHALL BE BUILT & LABELED PER UL 142 STANDARD FOR STEEL ABOVEGROUND TANKS FOR FLAMMABLE AND COMBUSTIBLE LIQUIDS UL FILE # MH5668

Surface Prep: Brush Blast
 Paint: Polane White
 Operating Pressure: Atmospheric
 Estimated Dry Weight: 1,050 lbs