



SCALE

MATERIAL DESCRIPTION

MODEL	KEY	QTY.	HORIZONTAL FIREGUARD SKID TANK
INNER DIAMETER			3'-2"
OUTER DIAMETER			4'-3"
INNER LENGTH			5'-0"
OUTER LENGTH			6'-0"
CAPACITY			300 GAL. (NOMINAL)
INNER GAUGE			10ga.
OUTER GAUGE			10ga.
CODE			UL 2085
SUPPORTS		2	10ga. FULL SKIDS, WITH END CAPS
FILL	A	1	2" #150 FULL COUPLING w/ PIPE EXTENTION
GAUGE	B	1	2" #150 FULL COUPLING w/ PIPE EXTENTION
PRIMARY E-VENT	C	1	4" SCH 40 NIPPLE (TOE)
SECONDARY E-VENT	D	1	4" SCH 40 NIPPLE (TOE)
WORKING E-VENT	E	1	2" #150 FULL COUPLING w/ PIPE EXTENTION
PRODUCT SUPPLY	F	1	2" #150 FULL COUPLING w/ PIPE EXTENTION
INTERSTITIAL MONITORING	G	1	2" #150 FULL COUPLING w/ SLOTTED PIPE
LIFT LUG	H	2	SMALL LIFT LUG w/ Repad (PHOENIX TYPE)
GROUND LUG	J	2	1/4"x2"x2" ANGLE w/1/2" HOLE
REMOTE GAUGE	K	1	2" #150 FULL COUPLING w/ PIPE EXTENTION
REMOTE GAUGE	R	2	2" #150 WELD FLANGE w/ Pipe plug seal welded after pour

TANK SHALL BE BUILT & LABELED PER UL 2085, STI FIREGUARD
UL FILE # MH21280

Surface Prep: Brush Blast
Paint: Polane White
Testing: Per UL 2085
Operating Pressure: Atmospheric
Estimated Dry Weight: 3,000lbs