



MATERIAL DESCRIPTION			
MODEL	KEY	QTY	HORIZONTAL DW FLAMESHIELD SKID TANK
Outer Diameter			3'-3"
Outer Length			5'-1/2"
Capacity			300 US Gallons Nominal
Inner Gauge			Per STI Flameshield - 12 Gauge
Outer Gauge			Per STI Flameshield - 12 Gauge
Code			STI FLAMESHIELD
Supports	A	2	Skids Full Length - 12 Gauge
Fill Opening	B	1	2" 150# Full Coupling W/Repad
Pump Opening	C	1	2" 150# Full Coupling W/Repad
Gauge Opening	D	1	2" 150# Full Coupling W/Repad
Op Vent Opening	E	1	2" 150# Full Coupling W/Repad
E-Vent Opening	F	1	4" Sch40 Nipple (Inner E-Vent) W/Repad
E-Vent Opening	G	1	4" Sch40 Nipple (Outer E-Vent)
Leak Monitor	H	1	2" Monitor Pipe (MNPT)
Remote Gauge	I	1	2" 150# Full Coupling W/Repad
Lift Lug	J	1	Small Lift Lug
Flameshield Labeling	L	Set	Labeled Per Flameshield F0001Appendix B

TANK SHALL BE BUILT & LABELED PER STI FLAMESHIELD F0001 STANDARD FOR FIRE TESTED TANK

Surface Prep: Brush Blast  
 Paint: Polane White  
 Testing: Per STI Flameshield  
 Operating Pressure: Atmospheric  
 Estimated Dry Weight: 710 lbs

