



Product Specification

FF5782NN

Fuel

Fleetguard® FF5782NN premium spin-on fuel filter that include NanoNet® high-performance filtration media reduce the number of harmful particles in the engine's fuel injectors. Its unique design delivers maximum engine life with premium protection and longer filter life, minimizing your operating costs.



Media Type	NanoNet
Thread Form	Unified National
Thread Pitch	12.0 threads Per Inch
Thread Diameter	2.25 inch
Largest OD	4.67 inch
Length	10.29 inch
Length / Overall Height	10.50 inch
Gasket Inside Diameter	4.00 inch
Gasket OD	4.74 inch
Thread Class	2B

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved