



Product Specification

LF14001NN

Lube, Spin-On

Fleetguard® LF14001NN premium lube spin-on filter features uses 2-in-1 NanoNet® and StrataPore® media to provide extended service intervals up to 100,000 miles while meeting or exceeding engine requirements. This media manufacturing technology provides the following advantages for our combination filter: higher particle removal efficiency, increased contaminant holding capacity, reduced flow restriction, especially under cold-start conditions, reduced CO2 footprint, and lower total cost of ownership.



| | |
|--------------------------------|------------|
| Media Type | NanoNet |
| Thread Pitch | 0.10 inch |
| BPV OPENING DP | No |
| Thread Form | Metric |
| Standpipe | No |
| Anti Drain Back Valve | No |
| Pressure Valve | No |
| Gasket OD | 4.72 inch |
| Length | 11.81 inch |
| Largest OD | 4.72 inch |
| Thread Diameter | 3.74 inch |
| Thread Class | 7H |
| Length / Overall Height | 11.81 inch |
| Gasket Inside Diameter | 3.99 inch |

This publication and all information contained or referenced in it (hereinafter "Publication") are provided as a convenience to Cummins Filtration customers "as is" without any warranties, express or implied, including warranties of merchantability, fitness for a particular purpose, or non-infringement of intellectual property. Cummins Filtration does not warrant the accuracy nor completeness of the Publication; may make changes to the Publication at any time without notice; and makes no commitment to update the Publication.

The Publication may refer to products, programs, or services that are not available in your country or local area. Consult Cummins Filtration directly for information regarding the products, programs, and services that may be available to you. Applicable law may not allow the exclusion of implied warranties, so the above exclusion may not apply to you. © 2023 Cummins Filtration Inc. All Rights Reserved