

Features and Benefits

Ease of Maintenance

- "SEEING IS BELIEVING[®]" technology – see when NOT to change the filter
- Clear bottom bowl with sturdy drain
- Low restriction check valve eliminates loss of prime when draining or changing the filter
- Robust, quick-acting drain for water and contaminant removal

Options

- Water-In-Fuel (WIF) sensor
- Electric Heater

High Performance

- Meets OEM efficiency requirements
- 67% increased media area to ensure greater protection of your engine
- 500+ hour service life recommendation
- Proprietary media ensures the best fuel/water separation available

Industrial Pro Engine Displacement Compatibility Matrix

Engine Displacement in Liters	Fuel Flow Rate Gal/hr (L/hr)	Short Single	Tall Single	Short Duplex	Tall Dual/Duplex	Tall Triple
5-19	40-100 (151-378)	X		X		
20-38	101-153 (382-479)	X		X		
39-50	154-206 (583-780)		X		X	X
51-60	207-264 (784-1000)		X		X	X

SHORT SINGLE



Applications

Diesel engines with flow rates up to 300 Gal/hr (1136 L/hr)

Specifications

Height: 20" (508 mm)
 Depth: 12" (305 mm)
 Width: 11.2" (284 mm)
 Weight (dry): 29 lb (13 kg)
 Fuel Capacity (w/o filter): 1.1 gal (4.3 L)

SHORT DUPLEX



Applications

Diesel engines with flow rates up to 300 Gal/hr (1136 L/hr)

Specifications

Height: 20.2" (513 mm)
 Depth: 12.3" (312 mm)
 Width: 32" (813 mm)
 Weight (dry): 58 lb (26.3 kg)
 Fuel Capacity (w/o filter): 2.5 gal (8.3 L)

TALL SINGLE



Applications

Diesel engines with flow rates up to 600 Gal/hr (2271 L/hr)

Specifications

Height: 28" (711 mm)
 Depth: 12" (305 mm)
 Width: 13.9" (352 mm)
 Weight (dry): 39 lb (17.7 kg)
 Fuel Capacity (w/o filter): 2.5 gal (9.5 L)

TALL DUAL



Applications

Flow rates up to 1200 Gal/hr (4543 L/hr)

Specifications

Height: 28" (711 mm)
 Depth: 12" (305 mm)
 Width: 23.8" (604 mm)
 Weight (dry): 90 lb (40.8 kg)
 Fuel Capacity (w/o filter): 5.0 gal (18.9 L)

TALL DUPLEX



Applications

Flow rates up to 1200 Gal/hr (4543 L/hr)

Specifications

Height: 28" (711 mm)
 Depth: 12" (305 mm)
 Width: 23.8" (604 mm)
 Weight (dry): 112 lb (50.8 kg)
 Fuel Capacity (w/o filter): 5.0 gal (18.9 L)

TALL TRIPLE



Applications

Flow rates up to 1800 Gal/hr (6813 L/hr)

Specifications

Height: 28" (711 mm)
 Depth: 12" (305 mm)
 Width: 35" (900 mm)
 Weight (dry): 135 lb (61.2 kg)
 Fuel Capacity (w/o filter): 7.5 gal (54.9 L)



A John M. Ellsworth Company

John M. Ellsworth Co., Inc.

P.O. Box 240072
 8700 West Bradley Road
 Milwaukee, WI 53224

800-333-3331 **PHONE**
 info@jmesales.com **E-MAIL**
 www.JMESales.com **WEB**