# SEA PRO®

## PRODUCT DATA SHEET

Fuel Filter and Fuel/Water Separator with NanoNet<sup>™</sup> Media for Marine Applications

## **Features and Benefits**

#### **Ease of Maintenance**

- Low restriction check valve eliminates loss of prime when draining or changing the filter
- Sturdy, quick-acting drain for water and contaminant removal
- Optional Water-In-Fuel (WIF) sensor available

### **Sea Pro Selection**

#### **High Performance**

- Meets OEM efficiency requirements
- · 67% increased media area to ensure greater protection of your engine
- 500+ hour service life recommendation
- · Proprietary media ensures the best fuel/water separation available

| Engine Displacement (in Liters) | Fuel Flow Rate Gal/hr (L/hr) | Single Short | Single Tall | Duplex Short | Duplex Tall |
|---------------------------------|------------------------------|--------------|-------------|--------------|-------------|
| 5-19                            | 40-100 (151-378)             | х            |             | Х            |             |
| 20-38                           | 101-153 (382-479)            | Х            |             | Х            |             |
| 39-50                           | 154-206 (583-780)            |              | Х           |              | Х           |
| 51-60                           | 207-264 (784-1000)           |              | Х           |              | Х           |

This table contains suggestions only. Exact requirements should be determined by consulting engine OEM or owner's manual information.

| SHORT SINGLE  | TALL SINGLE   | SHORT DUPLEX  | TALL DUPLEX   |  |
|---|---|---|---|--|
|   |   |   |   |  |
| Applications<br>Diesel engines with flow rates<br>up to 360 Gal/hr (1363 L/hr)  | Applications<br>Diesel engines with flow rates<br>up to 540 Gal/hr (2045 L/hr)  | Applications<br>Diesel engines with flow rates<br>up to 720 Gal/hr (2725 L/hr)  | Applications<br>Diesel engines with flow rates<br>up to 1080 Gal/hr (4088 L/hr)   |  |
| Specifications   Height: 19.2" (488 mm)   Depth: 8.8" (222 mm)   Width: 8.2" (208 mm)   Weight (dry): 31 lb (14.1 kg)   Fuel Capacity*: 1.2 gal (4.6 L)   *(w/o filter) * | Specifications   Height: 26.7" (678 mm)   Depth: 8.8" (222 mm)   Width: 8.2" (208 mm)   Weight (dry): 43 lb (19.5 kg)   Fuel Capacity*: 2.5 gal (9.3 L)   *(w/o filter) * | Specifications   Height: 24.7" (617 mm)   Depth: 11.1" (282 mm)   Width: 26" (660 mm)   Weight (dry): 80 lb (36.3 kg)   Fuel Capacity*: 2.4 gal (9.2 L) | Specifications   Height: 32.2" (808 mm)   Depth: 11.1" (282 mm)   Width: 26" (660 mm)   Weight (dry): 103 lb (46.7 kg)   Fuel Capacity*: 4.9 gal (18.6 L) |  |
| Certifications  | 1   | 1   |   |  |







John M. Ellsworth Co., Inc.

P.O. Box 240072 8700 West Bradley Road Milwaukee, WI 53224



800-333-3331 PHONE info@jmesales.com E-MAIL www.JMEsales.com WEB