Dixon® Fire Submittal Sheet

Brass Pin Lug Adapters

The Right Connection®

Pin Lug Hydrant

DFP2525F-D

Specifications

- ❑ Cast and/or forged brass; reducers
- ❑ Cast and/or forged brass; increasers
- ❑ Cast and/or forged brass; same size

NOTE: All adapters rated for **175 PSI** standard working pressure and include washers if needed.

Layout

- ❑ Rigid Male x Male
- ❑ Rigid Female x Male
- ❑ Female Swivel x Male
- ❑ Female Swivel x Female
- ❑ Double Female Swivel
- ❑ Female Swivel x Male w/ Poly Screen
- ❑ Female Swivel x Female w/ Poly Screen

NOTE: When ordering, the layout will follow (side 1 x side 2)

Side 1 Size & Thread Options

Nominal Size	Thread
3/4″	NST
1″	NPSH
1-1/2″	NPT
2″	GHT
2-1/2″	NYC (New York Corp)
3″	NYFD
3-1/2″	QST (Quebec Standard)
4″	CSA (Canadian Standard)
4-1/2″	WCT (Western Canada)
5″	NS1 (Nova Scotia)
6″	BCT (British Columbia)
	Other_____

Side 2 Size & Thread Options

Nominal Size	Thread
3/4″	NST
1″	NPSH
1-1/2″	NPT
2″	GHT
2-1/2″	NYC (New York Corp)
3″	NYFD
3-1/2″	QST (Quebec Standard)
4″	CSA (Canadian Standard)
4-1/2″	WCT (Western Canada)
5″	NS1 (Nova Scotia)
6″	BCT (British Columbia)
	Other_____

NOTE: Other local threads are available and are made to order. Ask Dixon Fire customer service for availability and lead times on combinations.

Replacement gaskets/washers are available upon request.

Dixon Fire

© 2023 DVCC • BAFDC_723