

Data Sheet

Brass Pipe Fittings



Brass Pipe Fittings

163	Hex Head Plug
165	Close Pipe Nipple
166	Long Pipe Nipple
169	90° Male Pipe Elbows
172	Male Union - NPSM x NPTF
174	Adapter-Male NPSM x Female NPT
176	Male Union - NPSM
207-BH	Bulkhead Anchor Coupling
211	Square Head Plug - Low Lead
213	Pipe Cap - Low Lead
219	Hex Socket Plug - Low Lead
228	Female Cross
302	90° Female Elbow
304	90° Street Elbow
306	45° Street Elbow
308	45° Female Pipe Elbow
322	Female Tee
324	Male Branch Tee
326	Street Tee
370	Male Hex Nipple
371	Female Hex Coupling
373	Reducer Bushing
375	Adapter-Female x Male
377	Reducing Adapter-Double Female
379	Male Reducing Hex Nipple

Applications

- For any low to medium pressure line connection and non-potable water service
- "LF" lead free option for potable water
- Use with brass, copper, or iron pipe

Sizes

- From 1/8" to 1" for most products
- Special sizes, configurations, and thread specifications available on request

Features

- NPSM unions and adapters also available
- 163 available products

Materials

- Brass: Alloy 360, 353 for straights
- Brass: Alloy 377 for forged shapes
- Brass: Alloy C3604 for extruded shapes
- Brass: Alloy CA2745, C46400, 260 and 270 for Lead Free
Brass (parts ending in LF)
- Plating: optional electroless nickel

Specifications

- Working pressure and temperature range **-65°F to 250°F (-53°C to 126°C)** at **1000 PSI**;
300 PSI on 211/219; **150 PSI** on 213
- Vacuum: Not rated

Approvals

- Meets functional requirements of SAE J530, J531
- Reference: 130137, 130138, 130139, 130140, 130238, 130239, 130339, 130424, 30425, 130438



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 **PHONE**
info@jmesales.com **E-MAIL**
www.jmesales.com **WEB**