

P.O. Box 240072 8700 West Bradley Road Milwaukee, WI 53224

800-333-3331 PHONE info@jmesales.com E-MAIL www.JMEsales.com WEB

Feature


Male NPTF x Hose Barb · Optional package quantity

Hose Fittings

Hose I.D.	Male NPTF	Brass		Lead-Free Brass ³	316 Stainless Steel	_
		Previous Part #	Part #	Part #	Part #	Qty
1/8"	1/8"	BN11	1020202C		RN11	100
	1/4"	BN122	1020204C			100
3/16"	1/8"	BN151	1020302C	1020302CLF	RN151	100
	1/4"	BN152	1020304C		RN152	100
1/4"	1/8"	BN21	1020402C	1020402CLF	RN21	100
	1/4"	BN22	1020404C	1020404CLF	RN22	100
	3/8"	BN23	1020406C		RN23	100
	1/2"	BN24	1020408C			50
5/16"	1/8"	BN251	1020502C		RN251	100
	1/4"	BN252	1020504C	1020504CLF	RN252	50
	3/8"	BN253	1020506C		RN253	50
3/8"	1/8"	BN31	1020602C	1020602CLF	RN31	100
	1/4"	BN32	1020604C	1020604CLF	RN32	100
	3/8"	BN33	1020606C	1020606CLF	RN33	50
	1/2"	BN34	1020608C	1020608CLF	RN34	25
	3/4"	BN36	1020612C			25
1/2"	1/4"	BN42	1020804C	1020804CLF	RN42	50
	3/8"	BN43	1020806C	1020806CLF	RN43	50
	1/2"	BN44	1020808C	1020808CLF	RN44	25
	3/4"	BN46	1020812C		RN46	25
5/8"	3/8"	BN53	1021006C		RN53	50
	1/2"	BN54	1021008C	1021008CLF	RN54	25
	3/4"	BN56	1021012C		RN56	25
3/4"	3/8"		1021206C			25
	1/2"	BN64	1021208C	1021208CLF	RN64	25
	3/4"	BN66	1021212C	1021212CLF	RN66	20
	1"		1021216C			25
1"	1/2"		1021608C			20
	3/4"	BN86	1021612C		RN86	20
	1"	BN88	1021616C ²		1021616SS ^{2,4}	10
	1-1/4"		1021620C ²			10
1-1/4"	3/4"	BN106	1022012C			10
	1"	BN108	1022016C ²			5
1-1/2"	1"		1022416C ²			5
	1-1/4"		1022420C ²			5



- ² Capped
- ³ NSF®/ANSI 61 certified Lead-Free Brass <=0.25% lead, Alloy C2745
- ⁴ Part is 316SS cast



Features

- · Extra long shank with additional barbs for better clamping surface; allows for two clamps to be installed
- 250 PSI @ 72°F (22°C); 150 PSI @ -40°F to 160°F (-40°C to 71°C)
- Temperature: -40°F to 160°F (-40°C to 71°C)

Hose I.D.	C360 Brass Part Number	Male NPTF	Number of Barbs	Pkg Qty
1-1/4"	1022012XL	3/4"	7	5
1-1/4"	1022016XL	1"1	7	5
1-1/4"	1022020XL	1-1/4"1	7	5
1-1/2"	1022416XL	1" ¹	8	5
1-1/2"	1022420XL	1-1/4"1	8	5

¹ Threads are capped





316 stainless steel



