

### SFSA30 - Storz x Female Swivel 30° Elbow - Rocker Lug

**Feature**

- Screens available for 4" and 5" heads, consult Dixon® for information

**Specification**

- Working pressure: 150 PSI at 70°F (21°C)



John M. Ellsworth Co., Inc.

P.O. Box 240072  
8700 West Bradley Road  
Milwaukee, WI 53224

800-333-3331 PHONE  
info@jmesales.com E-MAIL  
www.jmesales.com WEB

**Materials**

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5", and 6"



Storz Size	NST (NH) Female Swivel Thread	6061-T6 Forged Aluminum Part #
4"	4"	SFSA30-4040F
	5"	SFSA30-4050F
	6"	SFSA30-4060F
5"	3"	SFSA30-5030F
	4"	SFSA30-5040F
	4-1/2"	SFSA30-5045F
	6"	SFSA30-5060F

NOTE: Replacement washers can be found on page 840

### SFSA30 - Storz x Female Swivel 30° Elbow - Long Handle

**Materials**

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5", and 6"

**Specification**

- Working pressure: 150 PSI at 70°F (21°C)



Storz Size	NST (NH) Female Swivel Thread	6061-T6 Forged Aluminum Part #
4"	4-1/2"	SFSA30-4045F-LH
	5"	SFSA30-4050F-LH
	6"	SFSA30-4060F-LH

NOTE: Replacement washers can be found on page 840

### NCS-CSF - 150 lbs. Carbon Steel Flange x Storz

150# Flange	Storz	Carbon Steel Part #
4"	5"	NCS-CSF-STZ450
	6"	NCS-CSF-STZ460
5"	4"	NCS-CSF-STZ540
	5"	NCS-CSF-STZ550
6"	6"	NCS-CSF-STZ560
	4"	NCS-CSF-STZ640
	5"	NCS-CSF-STZ650
	6"	NCS-CSF-STZ660

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.

### NCS-CSF - 150 lbs. Carbon Steel Flange x Storz with Cap

150# Flange	Storz	Carbon Steel Part #
5"	6"	NCS-CSF-STZ650C
6"		NCS-CSF-STZ660C

NOTE: For flange dimensions, diagrams and additional information please reference dixonvalve.com.



N