



The Right Connection®

Data Sheet

Lubrication Products



Hose Assemblies:

GWH0800 – 8" assembly length
 GWH1200 – 12" assembly length
 GWH1800 – 18" assembly length
 GWH2400 – 24" assembly length
 GWH3600 – 36" assembly length
 GWH4800 – 48" assembly length
 GWH6000 – 60" assembly length

Note: Special lengths available for quote - 50 piece minimum

Couplers and Fittings:

GWHC - Grease hose coupler
 0010055C - 1/8-27 male NPT thread, drilled and chamfered base
 0010260C - 1/8-27 male NPT thread, solid base
 0010860C - 1/8-27 female NPT thread

Zerk Fittings:

GWHZ000 - Ball Check Zerk
 GWHZ045 - 45° Angle Ball Check
 GWHZ090 - 90° Angle Ball Check
 GWHZ400 - Ball Check Zerk 1/4 Tapered
 GWHZ445 - 45° Angle Ball Check 1/4 Tapered
 GWHZ490 - 90° Angle Ball Check 1/4 Tapered

Compliances:

- 3/16" hose meets SAE 100R1-AT specifications

Compatible Products:

- Compatible with all manually operated lubrication equipment using 1/8-27 connections and with standard Zerk grease fittings

Materials:

- Brass: alloy 360
- Steel couplers: 12L14, zinc plated
- Zerk: plated steel

Performance:

- Hose assemblies are rated 3000 PSI working pressure
- Temperature range: -20°F to 212°F

Applications / Markets:

- Industrial – processing plants, pulp and paper, food and beverage, assembly
- Mobile fleet – mining, construction, agriculture, trucking

Strengths / Features:

- US manufactured hose
- Seven standard hose assembly lengths available
- Optional special lengths available
- Three hose end fitting choices available on assemblies and separately
- Optional strain relief springs
- Optional retail packaging
- Two available coupler choices – ball check and full flow

Price Advantage:

- Substantial vs. Lincoln and Alemite for all products



John M. Ellsworth Co., Inc.

P.O. Box 240072
 8700 West Bradley Road
 Milwaukee, WI 53224

800-333-3331 **PHONE**

info@jmesales.com **E-MAIL**
 www.JMEsales.com **WEB**