Data Sheet

Dixon® Colored Double Jacket Fire Hose

The Right Connection®

800# Colored Double Jacket Fire Hose

Applications
- Industrial washdown
- Water discharge/transfer
- Municipal firefighting
- Standpipe/auto sprinkler supply line
- Master stream nozzle supply
- High pressure water transfer

Features
- Double jacket lined hose
- Optional colors: black, blue, green, orange, purple, red, tan, and yellow
- Other threads and configurations are available upon request, contact Dixon
- Uncoupled availability upon request
- Made in the USA

Specifications:
- Temperature range: **-60°F** to **112°F (-51°C** to **44°C)**
- Burst pressure: **1200 PSI** at ambient temperature **70°F (21°C)**
- Service test pressure: **800 PSI** at ambient temperature **70°F (21°C)**
- Working pressure: **400 PSI** at ambient temperature **70°F (21°C)**

Materials:
- All polyester outer jacket
- Thermoplastic polyurethane liner
- EPDM available upon special request

NOTE: Meets the following standards: NFPA 1960, UL-19, MIL-H-24606, and MIL A-A-59226

Coupled with Female and Male Expansion Couplings

Size	Length	Color	Rocker Lug Aluminum NST (NH) Part #	Rocker Lug Aluminum NPSH Part #
1-1/2”	50’	yellow	D815Y50RAF	D815Y50RAS
	100’		D815Y100RAF	D815Y100RAS
	50’	red	D815R50RAF	D815R50RAS
	100’		D815R100RAF	D815R100RAS
	50’	orange	D815OR50RAF	D815OR50RAS
	100’		D815OR100RAF	D815OR100RAS
2-1/2”	50’	yellow	D825Y50RAF	D825Y50RAS
	100’		D825Y100RAF	D825Y100RAS
	50’	red	D825R50RAF	D825R50RAS
	100’		D825R100RAF	D825R100RAS
	50’	orange	D825OR50RAF	D825OR50RAS
	100’		D825OR100RAF	D825OR100RAS

NOTE: 1-3/4”, 2”, 3”, 4”, and 5” sizes are available upon request

© 2025 DVCC

• Uncommon Excellence • Uncommon Excellence • Uncommon Excellence • Uncommon Excellence • Uncommon Excellence • Uncommon Excellence • Uncommon Excellence • Uncommon