

## **Product Specifications**



1C485020-63

FILTER HOUSING, DF 1100 MK

STANDARD

## **Attributes**

Model	DF
Housing Size	1100
Element Size	Size 1100
Element Type	DF
Connection Type	2 FNPT
Flow Rate Nominal (Air)	1100 m³/h
Differential Pressure Gauge	Econometer
Drain Type	UFM-P
Maximum Operating Pressure	232 psi (16 bar)
Maximum Operating Temperature	149 °F (65 °C)
Minimum Operating Temperature	34 °F (1 °C)

Filter Housing Material	Aluminum
Housing Gasket Material	Perbunan
Length	7.99 inch (203 mm)
Width	7.48 inch (190 mm)
Height	30.12 inch (765 mm)
Weight	15.87 lb (7.2 kg)
Drain Connection	G 1
PED 2014 68 EU	Yes
EAC	Yes
Packaged Dimensions	
Packaged Dimensions  Packaged Length	31.50 inch (80.010 cm)
	31.50 inch (80.010 cm) 14.17 inch (35.992 cm)
Packaged Length	
Packaged Length Packaged Width	14.17 inch (35.992 cm)
Packaged Length Packaged Width Packaged Height	14.17 inch (35.992 cm) 10.24 inch (26.010 cm)
Packaged Length  Packaged Width  Packaged Height  Packaged Weight	14.17 inch (35.992 cm) 10.24 inch (26.010 cm) 21.05 lb (9.548 kg)
Packaged Length  Packaged Width  Packaged Height  Packaged Weight	14.17 inch (35.992 cm) 10.24 inch (26.010 cm) 21.05 lb (9.548 kg)
Packaged Length  Packaged Width  Packaged Height  Packaged Weight  Packaged Volume	14.17 inch (35.992 cm) 10.24 inch (26.010 cm) 21.05 lb (9.548 kg)

The information contained herein is general in nature and may not reflect actual information regarding the part at time of shipment. Parts may originate in more than one country – the actual country of origin and HS Code will be reflected on the Commercial Invoice(s) that

accompanies the goods.

