

200 WESTSHORE BLVD • NEWARK, NY • 14513 • 800.265.8943 • FAA-FILTERS.COM

- As a standard in the compressor intake industry, this panel has provided complete protection for twenty years.
- Provides lower pressure drop, greater dust holding capacity, and longer life than the competition.



DESIGN SPECIFICATIONS PF2212020

| SIZE | Nominal 24" x 24" x 11 1/2" |
|----------------------|---|
| WEIGHT | 30 lbs |
| FILTER MEDIA | Water proof microglass fiber for higher efficiency filtration and extended service life. |
| FILTER MEDIA AREA | 134 sq. ft |
| FILTER EFFICIENCY | 99.97% of 2 Micron |
| DIRT HOLDING | 1135 Grams of ISO Medium test dust at 2500 CFM. |
| CHANGE OUT | 4" w.c. |
| COLLAPSE STRENGTH | >25" w.c. |
| FRAME | Galvaneal steel |
| SPACERS | Corrugated aluminum between each media pleat to maintain pleat opening and lower pressure drop. |
| SEALANT | Meia pack encapsulated top and bottom, with adhesive on sides. |
| REMOVAL RINGS | Corrosion resistant rings on each side of panel for ease of removal |
| CLEANABILITY | Not cleanable |

