

	STANDARD FLOW, STANDARD-DUTY NOZZLES			STANDARD FLOW, HEAVY-DUTY NOZZLES		SUB-ZERO, HEAVY-DUTY NOZZLES	
							
PART NUMBER	SDN075RAN	SDN075GAN	SDN100GAN	N075UAU10	N075DAU10	FRNA075DAU10	FRNA100DAU00
Short Description	STANDARD DUTY, ¾" GASOLINE AUTOMATIC NOZZLE (RED)	STANDARD DUTY, ¾" DIESEL AUTOMATIC NOZZLE (GREEN)	STANDARD DUTY, 1" DIESEL AUTOMATIC NOZZLE (GREEN)	¾" GASOLINE AUTOMATIC NOZZLE (RED)	¾" GASOLINE AUTOMATIC NOZZLE (GREEN)	¾" SUB-ZERO AUTOMATIC NOZZLE	1" SUB-ZERO AUTOMATIC NOZZLE
Max Flow Rate	14.5 GPM	14.5 GPM	25 GPM	14.5 GPM	14.5 GPM	15 GPM	25 GPM
Cover Color	RED	GREEN	GREEN	RED	GREEN	BLUE	BLUE
Inlet Size (ID)	¾" NPT	¾" NPT	1" NPT	¾" NPT	¾" NPT	¾" NPT	1" NPT
Spout Size (OD)	13/16"	15/16"	1 - 1/8"	13/16"	15/16"	15/16"	1 - 3/16"
Max Working Pressure	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI
Pressure Drop	17.0 PSI @ 14.5 GPM	12.0 PSI @ 14.5 GPM	12.0 PSI @ 25 GPM	18.3 PSI @ 14.5 GPM	12.3 PSI @ 14.5 GPM	12.3 PSI @ 15 GPM	8 PSI @ 25 GPM
Minimum Operation Temperature	-20° F	-20° F	-20° F	-20° F	-20° F	-40° F	-40° F
Integral Spout Spring	YES	YES	YES	YES	YES	YES	YES
Automatic Shutoff	YES	YES	YES	YES	YES	YES	YES
Number of Latch Positions	3	3	3	2	2	2	2
No-Pressure, No-Flow Functionality	YES	YES	YES	YES	YES	YES	YES
No-Pressure, No-Flow Limit	2.4 TO 3.5 PSI	2.4 TO 3.8 PSI	2.0 TO 3.5 PSI	3.9 TO 4.0 PSI	3.4 TO 3.5 PSI	2 TO 3 PSI	2 TO 3 PSI
Seal Material	Fluorocarbon	Fluorocarbon	Fluorocarbon	Fluorocarbon	Fluorocarbon	Cold Weather Fluorocarbon	Cold Weather Fluorocarbon
Fluid Compatibility	GASOLINE, DIESEL, BIODIESEL (TO B20), E10, & KEROSENE			GASOLINE, DIESEL, BIODIESEL (TO B20), E10, & KEROSENE		GASOLINE, DIESEL, BIODIESEL (TO B20), E10, & KEROSENE	
Certifications	UL/cUL	UL/cUL	UL/cUL	UL/cUL	UL/cUL	UL/cUL	UL/cUL

	HIGH FLOW, HEAVY-DUTY NOZZLES		ULTRA HIGH-FLOW, HEAVY-DUTY NOZZLES		
					
PART NUMBER	N100DAU12	N100DAU12G	N100DAU13	N100DAU13G	N100DAU13Y
Short Description	1" DIESEL AUTOMATIC NOZZLE (RED)	1" DIESEL AUTOMATIC NOZZLE (GREEN)	1" ULTRA HIGH-FLOW DIESEL AUTOMATIC NOZZLE (RED)	1" ULTRA HIGH-FLOW DIESEL AUTOMATIC NOZZLE (GREEN)	1" ULTRA HIGH-FLOW DIESEL AUTOMATIC NOZZLE (YELLOW)
Max Flow Rate	25 GPM	25 GPM	40 GPM	40 GPM	40 GPM
Cover Color	RED	GREEN	RED	GREEN	YELLOW
Inlet Size (ID)	1" NPT	1" NPT	1" NPT	1" NPT	1" NPT
Spout Size (OD)	1 - 1/8"	1 - 1/8"	1 - 3/16"	1 - 3/16"	1 - 3/16"
Max Working Pressure	50 PSI	50 PSI	50 PSI	50 PSI	50 PSI
Pressure Drop	13.8 PSI @ 25 GPM	13.8 PSI @ 25 GPM	8 PSI @ 25 GPM	8 PSI @ 25 GPM	8 PSI @ 25 GPM
Minimum Operation Temperature	-20° F	-20° F	-20° F	-20° F	-20° F
Integral Spout Spring	YES	YES	YES	YES	YES
Automatic Shutoff	YES	YES	YES	YES	YES
Number of Latch Positions	3	3	3	3	3
No-Pressure, No-Flow Functionality	YES	YES	YES	YES	YES
No-Pressure, No-Flow Limit	3.8 TO 3.9 PSI	3.8 TO 3.9 PSI	2 TO 3 PSI	2 TO 3 PSI	2 TO 3 PSI
Seal Material	Fluorocarbon	Fluorocarbon	Fluorocarbon	Fluorocarbon	Fluorocarbon
Fluid Compatibility	GASOLINE, DIESEL, BIODIESEL (TO B20), E10, & KEROSENE		GASOLINE, DIESEL, BIODIESEL (TO B20), E10, & KEROSENE		
Certifications	UL/cUL	UL/cUL	UL/cUL	UL/cUL	UL/cUL