



ENGINEERING & TECHNICAL DATA — Bendway® Plus

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
3	.47	.006	13	N/A	29	18
4	.64	.006	15	N/A	29	15
5	.8	.006	17	N/A	29	13
5.5	.85	.006	19	N/A	29	12
6	.92	.006	24	N/A	29	11
7	1.06	.006	26	N/A	29	9.5
8	1.2	.006	28	N/A	29	8.5
9	1.38	.006	30	N/A	29	8
10	1.55	.006	32	N/A	29	6
11	1.69	.006	34	N/A	29	5.5
12	1.83	.006	37	N/A	29	5

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Manufactured using 316Ti Stainless Steel in a patented roll lock construction

Temperature Range: up to 1650°F

Standard Color: Silver

Standard Lengths: 25 Feet (3_ to 8_), 15 Feet (9_ to 12_)



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 **PHONE**

info@jmesales.com **E-MAIL**
www.JMEsales.com **WEB**