



ENGINEERING & TECHNICAL DATA — Flexadux TR® E-7

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
4	.44	.030	3.5	3:1	24	22
6	.73	.030	6	3:1	18	15
8	1	.030	8	3:1	12	7

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Medium weight polyethylene alloy hose with UV additive reinforced with a bronze coated spring steel wire helix

Temperature Range: -40°F to 160°F

Standard Color: Clear

Standard Lengths: 25 Feet

Disclaimer: The proper use and maintenance of hose and/or ducting manufactured by Flexaust is the sole responsibility of the purchaser and ultimate user of the product. This information is presented as a general guide only. The number of variables which can be present in any application make firm recommendations impossible.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 **PHONE**

info@jmesales.com **E-MAIL**
www.JMEsales.com **WEB**