



ENGINEERING & TECHNICAL DATA — Flexadux® PU Flx-Thane® SDX-20

INSIDE DIAMETER (IN)	APPROX. WEIGHT (LBS/FT)	WALL THICKNESS (IN)	CL BEND RADIUS (IN)	COMPRESSION RATIO	NEGATIVE PRESSURE (IN/HG)	WORKING PRESSURE (PSI)
2	.25	.015	2	3:1	29	30
2.5	.35	.020	2.75	4:1	29	30
3	.4	.020	3.25	4:1	29	30
4	.5	.020	3.75	4:1	24	22
5	.6	.020	4.5	4:1	13	18
6	.7	.020	5.25	4:1	8	15
7	.8	.020	5.88	5:1	8	10
8	.9	.020	6.5	5:1	2	7
9	1	.020	7	5:1	2	7
10	1.2	.020	7.5	5:1	2	7
12	1.4	.020	9	5:1	1.7	6
14	1.6	.020	12	5:1	1.1	5
16	1.8	.020	14	5:1	.7	4.6
18	2	.020	16	5:1	.5	4.1

Technical data based on 2 ft. straight lengths of hose @ 72°

Construction: Self-extinguishing light weight static dissipative polyurethane hose reinforced with a bronze coated spring steel wire helix

Temperature Range: -65°F to 200°F

Standard Color: Clear

Standard Lengths: 25 & 50 Feet

- Surface resistivity level: 10^8 - 10^{10} Ohms/Square
- Listed as UL 94V-2 flame retardant



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 **PHONE**

info@jmesales.com **E-MAIL**
www.JMESales.com **WEB**