

DEF METER T32P-08B

Instruction Sheet

Fluid Compatibility

For use with Diesel Exhaust Fluid (DEF)

Not compatible with petroleum-based liquids.
DO NOT USE WITH FLAMMABLE LIQUIDS

Power Supply:

2x AAA batteries located under back cover of meter.

Operation Instructions:

Turn Meter ON:

- The meter will automatically turn on and begin totalizing when flow through meter occurs.
To manually turn meter ON: Short press either RESET or MENU button.
- Note: Meter will automatically turn OFF display when left idle for 90 seconds.

Set Unit of Measure:

- Press and hold RESET and MENU buttons together for 5 seconds. When unit of measure icon flashes use RESET button to select between GAL, PT, QT, L. Hold MENU button for 3 seconds to save the unit of measure setting.

Reset Batch Total (Large Digit Display)

- To Reset Batch Total short press RESET button.

Select the display of Flow Rate or Accumulative Total:

- Short press MENU button to toggle between display of Flow Rate or Accumulative Total.

Reset Accumulative Total (Small Digit Display)

- Press and hold RESET button for 5 seconds. This will reset both Accumulative and Batch totals to zero.



Specifications:

Flow Range	3 - 32 GPM (12-120 L/min)
Accuracy (% of Reading)	+/- 1%
Technology	Turbine
Pressure Rating	43.5 PSI (3 bar)
Operating Temperature	23° F to 104° F (-5° C to 40° C)
Meter Housing Material	Polyamide
Wetted Materials	Borosilicate Glass Polyamide Stainless Steel Zirconia Ceramic
Inlet	G1, 1-inch BSPP (Male)
Outlet	G1, 1-inch BSPP (Male)