GASOILA® Lube-It All



TECHNICAL DATA

Description

Lube-It All is a high viscosity oil that clings to moving parts. Foaming action penetrates close tolerances of chain drive bushings and pins to provide long-lasting lubrication. Reduces friction wear on moving parts and in metal-to-metal applications. The 'moly' additive improves its capacity to handle greater pressure requirements of start-up stress.

Туре

A high viscosity oil that clings to moving parts, fortified with Molybdenum, Moly to handle greater pressure.

Typical Uses

Chain drives and pins, Forklift trucks, Link and roller assemblies, Machinery, Work-stand rollers, Assembly lines, Packaging equipment, Motorcycle and bicycle chains, Sprockets, Clippers, Cutter bars, Chain saws, Bushings, Hoist chains, Conveyors.

Substrates

Any Ferrous metal.

Directions

Liberally coat the parts to be loosened. Allow a few minutes for penetration. If needed re-apply.

Packaging 1, 6 and 12 ounce aerosol cans (by weight)

Safety Extremely Flammable

Shelf Life One year in original containers, when stored at room temperature at or below 80°F (27°C)

Color A clear liquid with suspended additives

Odor Mild Solvent

Clean Up Hand cleaner or other mild solvent

For Chemical Emergency, Spill, Leak, Fire, Exposure or Accident Call: CHEMTREC - Day or Night. 1-800-424-9300 KEEP OUT OF THE REACH OF CHILDREN

Product Data Sheet

Characteristics:

APPEARANCE Light Amber

PROPELLANT: Carbon Dioxide

ODOR: Mild Solvent or Petroleum

WT./GAL.: 6.838

SPECIFIC GRAVITY: 0.82

PAINTABLE No

% VOC AEROSOL: 22.5%

V.O.C. COMPLIANT CALIFORNIA: Yes

FLAMMABLE: Yes

FLASH POINT: 166°F (74°C) (closed cup method)

The information presented is in good faith, but no warranty is given, nor are results guaranteed. Federal Process has no control over physical conditions surrounding application conditions. Federal Process disclaims any liability for untoward results.



CLEVELAND, OHIO | 216.464.6440 • 800.846.7325

WWW.gasoila.com MSDS Sheets Available Online #DS-LA

2013