



REVISIONS			
REV.	DESCRIPTION	DATE	APPROVED
8			

30" +1/2"
-1/4" OAL

24 $\frac{15}{16}$ " Hose Length

ITEM #	QTY.	PART NUMBER	DESCRIPTION	MATERIAL	WEIGHT
1	1	HOSE	300 Series Stainless HYDROFORMED Corrugated Hose	Stainless Steel	1.42
2	1	BRAID	300 Series Stainless Steel	Stainless Steel	0.12
3	2	BRAID COLLAR	0.05" Thick	Stainless Steel	0.09
4	1	2" MALE SWIVEL	2" Male Swivel, 2"x11-1/2" Thread, 2.38" Hex	Carbon Steel	0.93
5	1	2" ELBOW	2" Short Radius Elbow, Sch. 40	Carbon Steel	0.52
6	1	2" FEMALE SWIVEL	2" Female Swivel, 2"x11-1/2" Thread, 2.38" Hex	Carbon Steel	2.41



HOSE MASTER Inc.

1233 East 222nd Street • Cleveland, Ohio 44117
(800) 221-2319 • Fax: (216) 481-7557 • www.hosemaster.com
Locations: **Cleveland • Houston**

Registered to:
ISO 9001 : 2000



Projection:	Customer: Hose Master Inc.	Prepared By: kannk
	Reference: Fire-Shield - 2" Male Swivel x 2" 90 Degree Female Swivel x 30" OAL	CALC. WEIGHT: 6 lbs. Date: 9/24/2009
	Description: 2" ID x 30" OAL 300 Series Stainless HYDROFORMED Corrugated Hose covered by 300 Series Stainless Braid. UL Approved 2" Male Swivel Connector x 2" ID 90 Degree Female Swivel Connector	

FSSWE0200x30

Rev.: -
SHEET
1 OF 1