



## **HEAVY DUTY HOSE SUSPENSION SADDLES**

- Offer an efficient and effective protection against accidents, environmental damages and wastefulness;
- Maintenance-free service;
- Its special design protects hoses from slipping and kinking, reduces premature hose failures and decreases the costs of hose replacements;
- Reduce risks to personnel working under or near a hoisted hose;
- Offers immediate protection without special implementation tools;
- Produced to meet the standard requirements of a wide quality control programme as well as the standard requirements of independent regulatory bodies;
- Operating at temperatures ranging from -40c° to 130c°, age-resistant and hydrolysis free;
- Anti-spark, isolating and anti-static construction;
- Resistant to fuel, oil, jet-fuel, most chemicals and petrol chemicals;
- Slings are easily replaceable when worn-out or damaged;
- Sizes ranging from 1 to 12 inches.

## Application of hose saddles:

## SIZES 1" TO 4"

Gas stations, hydraulic hoses, industrial hoses and cables, pumping, mines and power cables, construction sites etc.

## SIZES 6" TO 10"

Dock hoses on offshore platforms, fish transfer hoses (reduces dents considerably), vacuum hoses, material handling hoses, food grade hoses etc.

Туре D





John M. Ellsworth Co., Inc.

P.O. Box 240072 8700 West Bradley Road Milwaukee, WI 53224 800-333-3331 PHONE 800-563-8848 FAX info@jmesales.com E-MAIL www.JMEsales.com WEB

PAYL **HEIGHT** WEIGHT I.D. LENGTH PICTURES **ITEMS** OAD HOSE KG 1"/ **VAL 100** 1,30kg 364 ED METAL 2,5cm 46cm 4cm D.RING **VAL 125** 1,25" / ED METAL 3.1cm 364 47cm 5.5cm 1,50kg D.RING **VAL 150** 1,5" / 1,60kg ED METAL 3,8cm 364 51cm 5cm D.RING **VAL 200** 2" / ED METAL 364 34cm 6.5cm 1,00kg 5,0cm D.RING VAL 200 D 2" / METAL 364 34cm 6.5cm 1,00kg 5.0cm D.RING 2" / 34cm 6.5cm VAL 200 H 682 1,00kg HOOK-EYE 5,0cm **VAL 300 D** 3" / METAL 364 33.5cm 9.5cm 1,20kg 8,0cm D.RING 3" / 682 33.5cm 9.5cm 1,20kg VAL 300 H HOOK-EYE 8,0cm **VAL 400 D** 4" / METAL 364 31.5cm 12cm 1.80kg 10,0cm D.RING 4" / VAL 400 H 31.5cm 12cm 682 HOOK-EYE 10,0cm 1.80kg 6" / VAL 600 H 3.640 55.5cm 17.5cm 5,5kg HOOK-EYE 15,0cm 12,00kg 8" / VAL 800 H 5.455 77.5cm 24cm HOOK-EYE 20,0cm **VAL 1000** 10" / H HOOK-6820 104cm 27cm 20,00kg 25,0cm EYE **VAL 1200** 104cm 27cm 20,kg 12"/ H HOOK 6.820 30.0cm EYE