



View Up To Date Info



◀ SCAN OR VISIT
[KOA.link/
T253AA](https://KOA.link/T253AA)



**FOR APPLICATIONS INVOLVING
INDUSTRIAL ACID CHEMICALS AND
ALCOHOLS, PLEASE REFER TO T5050G
AND T5090E CHEMICAL HOSES**

T253AA Series

150 PSI EPDM Layflat Water Discharge Hose

GENERAL APPLICATIONS

- High pressure, 150 PSI lay flat type hose for general industrial construction and irrigation

CONSTRUCTION

Tube – Black EPDM

Reinforcement – High tensile textile cords – 2 spirals up to 4", 4 spirals above 4"

Cover – Black EPDM – abrasion and ozone-resistant

WORKING PRESSURE

Constant Pressure –
10 Bar (150 PSI)

SERVICE TEMPERATURE RANGE

-22°F (-30°C) to +176°F (+80°C)

BRANDING

ALFAGOMMA – ITALY – 253 10 Bar (150 PSI) EPDM WATER DISCHARGE (in green letters)

Series Number	ID		OD		Max. Working Pressure (psi)	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)			
T253AA150	1 1/2	38	1.81	46	150	100	0.37
T253AA200	2	51	2.32	59	150	100	0.50
T253AA250	2 1/2	63	2.80	71	150	100	0.60
T253AA300	3	76	3.31	84	150	100	0.86
T253AA400	4	102	4.33	110	150	100	1.19
T253AA600	6	152	6.38	162	150	50/100	2.00
T253AA662	6 5/8*	168	7.01	178	150	50/100	2.17
T253AA800	8	203	8.46	215	150	50/100	2.82
T253AA1000	10	254	10.63	270	150	50/100	5.11
T253AA1200	12	305	12.56	319	150	50	5.93

* 6 5/8" referred to as Elephant Trunk Hose – Ideal for "Irrigation Boots."

COUPLING SUGGESTIONS: Quick-Acting, pin lug, short shank couplings or combination nipples attached with single bolt, double bolt, wire or band type clamps.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 **PHONE**

info@jmesales.com **E-MAIL**
www.JMEsales.com **WEB**