




ORV™ Series

Standard-Duty, Oil Resistant, PVC Suction Hose

GENERAL APPLICATIONS

- Environmental cleanup
- Oil skimming
- Oil slurries
- Oil suction
- Vapor recovery – hydrocarbon emissions

CONSTRUCTION

Oil resistant PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

5°F (-15°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*

View Up To Date Info



◀ SCAN OR VISIT
**KOA.link/
ORV**



FEATURES AND ADVANTAGES

- **Oil Resistant PVC Tube** – Made with special oil resistant compounds which exhibit medium resistance to oil and other hydrocarbons.
- **Smooth Outer Cover** – Provides increased pressure rating and smooth surface for banding.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
ORV075	3/4	19.0	1.01	25.6	100	60	28	26	3	100	0.19
ORV100	1	25.4	1.26	32.0	80	50	28	26	3	100	0.24
ORV150	1 1/2	38.1	1.76	44.6	60	40	28	24	5	100	0.35
ORV200	2	50.8	2.32	59.0	60	40	28	24	7	100	0.55
ORV300	3	76.2	3.41	86.7	65	40	28	22	10	100	1.09

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.
- Chemical Resistant Guides (for details see pages 108-109)

COMPLIANCES (for details see page 87)
Phthalate Free (10), **RoHS** (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.