



WOR™ Series

Standard-Duty, Oil Resistant, PVC Suction Hose

GENERAL APPLICATIONS

- Environmental clean-up
- Oil skimming
- Oil slurries
- Oil suction
- Vapor recovery – hydrocarbon emissions

CONSTRUCTION

Oil resistant PVC tube with rigid PVC helix

SERVICE TEMPERATURE RANGE

5°F (-15°C) to +150°F (+65°C)*

**Actual service temperature range is application dependent.*



FEATURES AND ADVANTAGES

- **Oil Resistant PVC** – Made with special oil resistant compounds which exhibit medium resistance to oil and other hydrocarbons.
- **Convuluted Outer Cover** – Provides increased hose flexibility.

Series Number	ID		OD		Working Pressure (psi)		Vacuum Rating Hg (in)		Min. Bending Radius (in) at 68°F	Standard Length (ft)	Weight (lbs/ft)
	(in)	(mm)	(in)	(mm)	at 68°F	at 104°F	at 68°F	at 104°F			
WOR150	1 1/2	38.1	1.92	48.8	50	25	28	24	3	100	0.31
WOR200	2	50.8	2.40	61.0	40	20	28	24	4	100	0.50
WOR300	3	76.2	3.64	92.5	40	20	28	24	6	100	1.17
WOR400	4	101.6	4.72	119.9	35	18	28	22	10	100	1.74

NOTES:

- Service life may vary depending on operating conditions and type of material being conveyed.
- Chemical Resistant Guides (for details see pages 108-109)

COMPLIANCES (for details see page 87)

Phthalate Free (10), **RoHS** (11)

Because we continually examine ways to improve our products, we reserve the right to alter specifications or discontinue products without prior notice.