

L.B.WHITE

Boss 400 DF

NEW BOSS[™] 400 DF 400,000 btu/hr direct fired heater

Push big heat into large, wide open job sites and warehouses with high CFM and 99% fuel efficiency

Easy-open, rust resistant Tri-shield™ case

Cool-end handle —

Control Panel with: • Electronic ignition • Diagnostics • Vent Mode • Volt Meter

JOB SITE TOUGH

Indoor/outdoor rated

■ Rust resistant Tri-shield[™] case

Thermostat

Construction-grade, no-flat wheels

LOADED WITH FEATURES THAT BENEFIT OWNER AND OPERATOR

NO PARTS OR DOWNTIME TO:

Change fuel
Confirm onsite voltage
Manage heat output

MORE THAN HEAT



Vent mode feature moves air like a fan



Diagnostic light for quicker troubleshooting

TRULY PORTABLE

Cool-end handle
No-flat wheels
Stackable



10-side case for easy inside-out access



Stackable



Stands on end

800-345-7200 / 608-783-5691 www.lbwhite.com



BOSS[™] 400 DF HEATER

BOSS™	400 DF
BTU/H RATING	400,000
BLOWER FAN OUTPUT (CFM)	2,500
HEAT TYPE	DIRECT FIRED*
FUEL TYPE	DUAL FUEL - LP/NG
IGNITION TYPE	SPARK
FUEL CONSUMPTION LP GAS MIN./MAX. (LBS./HR.)	18.56
FUEL CONSUMPTION NAT. GAS MIN./MAX. (CU.FT./HR.)	400
INLET GAS PRESSURE LP MIN./MAX. (IN W.C.)	7"/13.5"
INLET GAS PRESSURE NG MIN./MAX. (IN W.C.)	7"/13.5"
AMPS (STARTING/CONTINUOUS OPERATION)	27.2/7.1
ELECTRIC SUPPLY (VOLTS/HZ/PHASE)	120/60/1
MOTOR HORSEPOWER	1/2 HP
LENGTH (IN.)	49 7/8" (WITH HANDLE)
WIDTH (IN.)	21.25
HEIGHT (IN.)	22.5
UNIT WEIGHT (LBS.)	125.0
BUILT-IN VOLT METER	YES
BUILT-IN THERMOSTAT	YES
VENT MODE	YES
DUCTABLE	NO
OMNI CERTIFIED U.S./CANADA	ANSI Z83.7-2017 / CSA 2.14-2017
* For use in self-ventilated area only.	TWO YEAR WARRANTY





WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS

411 Mason Street, Onalaska, WI 54650 (800) 345 7200 (608) 783 5691 (608) 783 6115, fax www.lbwhite.com





© 2018 L.B. White Co. All rights reserved. All specifications are subject to change without notice.