Solidly indirect delivering clean, dry heat.

- Highest BTU in the class at 230,000 btu/hr
- Delivers high CFM with 12" outlet and 16" inlet combination
- Operator-friendly control panel with:
 - ·Onboard voltmeter
 - ·Hour meter that clocks actual runtime (heat mode only)
 - ·Status and diagnostic lights
- Aids fuel efficiency with thermostat control, vent mode, and recirculation options
- One-person portability
- Efficient storage options with no-flat wheels and frame designed to stand-on-end
- **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- Only two-year warranty in the class

Model Options

Oil - Diesel #1 and 2 Dual Fuel - LP and NG

Accessories (Sold Seperately)

Vent Pipe Extension
Rain Cap
Regulator for DF model only
Gas Hose for DF model only
Duct (12" or 16")
Thermostat with 25 ft cord
Genisys Contractor Display Tool





FOREMAN ™	230 DF	230 OIL
BTU/H RATING	230,000	230,000
BLOWER FAN OUTPUT (CFM)	1900	1900
FUEL TYPE	LP/NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX		
LP (LBS./HR)	10.6	
NG (CU.FT/HR)	230	
DIESEL 1 OR 2 (G/HR)		1.7
INLET GAS PRESSURE MIN./MAX.		
LP (IN W.C.)	7/13.5	
NG (IN W.C.)	7/13.5	
PUMP PRESSURE (PSI)		180
BURNER TYPE	BECKETT®	BECKETT®
TANK SIZE		33
OUTLET STATIC PRESSURE (IN W.C.)	2.5	2.5
OUTLET DUCT DIAMETER (INCH)	12	12
RECIRCULATION DUCT DISTANCE MAX (FEET)	25	25
RECIRCULATION DUCT DIAMETER (INCH)	16	16
MOTOR HORSEPOWER	1/2	1/2
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)	120/60/1	120/60/1
RUNNING AMPS	9	9
UNIT WEIGHT (LBS)	307	396
UNIT LENGTH (IN)	60.2	60.2
UNIT WIDTH (IN)	26.6	26.6
UNIT HEIGHT (IN)	43.3	43.3
SHIP WEIGHT (LBS)*	421	516
SHIP LENGTH (IN)	64.0	64.0
SHIP WIDTH (IN)	31.3	31.3
SHIP HEIGHT (IN)	49.9	49.9
THIRD PARTY CERTIFIED TO ANSIZ83.7/CSA 2.14-2017	YES	YES
	TWO YEAR WARRANTY	



Cancer and reproductive harm. See www.P65Warnings.ca.gov.









