

FOREMAN®	500 DF	500 OIL
BTU/H RATING	500,000	500,000
FUEL TYPE	LP, NG	DIESEL
FUEL CONSUMPTION LP MAX. (LBS./HR.)	23.0	-
FUEL CONSUMPTION NG MAX. (CU.FT./HR.)	500.0	-
FUEL CONSUMPTION DIESEL 1 OR 2 MAX. (GAL./HR.)		3.6
INLET GAS PRESSURE LP MIN./MAX. (IN W.C.)	8/13.5	-
INLET GAS PRESSURE NG MIN./MAX. (IN W.C.)	8/13.5	-
OUTLET STATIC PRESSURE (IN W.C.)	2.5	2.5
TANK SIZE / OPERATING TIME	-	42 GAL / 11 HRS
BLOWER FAN OUTPUT (CFM)	3,457	3,457
AMPS (STARTING / CONTINUOUS OPERATION)	32.2 / 13.5	32.2 / 13.5
ELECTRIC SUPPLY (VOLTS/HZ/PHASE)	120/60/1	120/60/1
MOTOR HORSEPOWER	1.5	1.5
LENGTH (IN.)	94.0	94.0
WIDTH (IN.)	32.0	32.0
HEIGHT (IN.)	53.0	53.0
SHIPPING WEIGHT (LBS.)	850.0	1000.0
BURNER TYPE	RIELLO	BECKETT
SINGLE POINT LIFTING BALE	S	S
FORK LIFT HOLES	S	S
SELF-DIAGNOSTIC SYSTEM	S	S
TWO 12" OUTLETS*	S	S
20" AIR RECIRCULATION INLET	S	S
U.S./CANADIAN CERTIFICATION	YES	YES
	TWO YEAR WARRANTY	





S=Standard 0=Optional

*One 16" air outlet sold separately.



CA RESIDENTS:

WARNING

Cancer and reproductive harm. See www.P65Warnings.ca.gov.

CONTRACTOR APPROVED

WORLD PROVIDER OF INNOVATIVE HEATING SOLUTIONS

