



L.B.WHITE



CLASSIC™ Forced Air Heaters

60
115

The best value in high quality, dependable swine confinement heating.

Setting the standard in swine confinement heating for more than 65 years, L.B. White Classic pilot light heaters offer simple, reliable operation for years of worry-free performance.

Dependable, Economical Heat

A proven performer from gestation to finishing, L.B. White's Classic forced air heaters offer a wide range of heat outputs, safety features and installation options to fit your confinement needs:

- Highly efficient, pilot light design
- Choice of models
 - 60,000 Btu/h
 - 115,000 Btu/h
- Choice of propane or natural gas
- Versatile indoor mount options

In addition, L.B. White Classic heaters are available in certified models to meet or exceed U.S. and Canadian CSA safety standards.

Easy Operation, Low Maintenance Design

L.B. White Classic heaters are designed with easy installation and maintenance in mind. Each L.B. White Classic comes equipped with eyebolts and chains for easy hanging. Panels remove effortlessly for quick access to components and pilot orifices are easy to clean with our quick take-apart pilot assembly.

Durable Materials

L.B. White's Classic heaters are built to withstand the corrosive elements of even the toughest swine confinement operations. Sealed caps on the solenoid and pilot control fully protect gas valves from heavy dust, dirt and moisture. And the Classic's high quality, corrosion resistant components and solid case construction mean your L.B. White heater will provide years of reliable operation.

Knowledgeable, Friendly Technical and Customer Support

With over 65 years of heating experience and a full line of forced air and radiant heating solutions, only L.B. White offers you the product quality, technical expertise and knowledgeable customer support you can count on to help you design the best heating solution for your needs.



For more information about how L.B. White Classic pilot light heaters can help you improve production and reduce costs, please contact your local L.B. White representative or contact us directly toll-free at **800-345-7200** or **608-783-5691**.

Classic™ Forced Air Heater Specifications

Models:	Classic 60(N)	Classic 115(N)
Rating:		
Maximum Input (Btuh)	60,000	115,000
Heater Configuration:	Pilot Ignition	Pilot Ignition
Fuel Consumption (max.):		
Liquid Propane Gas (lbs./hr.)	2.8	5.3
Natural Gas (cu. ft./hr.)	60.0	115
Heated Air Output (CFM)	250	480
Inlet Gas Supply Pressure:		
Heater operates at appliance category pressure requirements of host country	Yes	Yes
Electrical Supply (Volts / Hz / Phase):	115 / 60 / 1	115 / 60 / 1
Amps (Starting / Cont. Oper.)	3.0 / 1.0	6.0 / 1.6
Cabinet Material	Steel with Tri-shield Coating*	Steel with Tri-shield Coating*
Dimensions (in.):		
Length	21.0	23.0
Width	11.0	17.0
Height	24.0	24.0
Net Weight (lbs.)	55.0	90.0
Shipping Weight (lbs.)	61.0	100.0
Accessories:		
Chain Hanging Kit	Standard	Standard
Air Diverter	Optional	Optional
Second Stage Regulator	Optional	Optional
Thermostat	Optional	Optional
Sediment Trap	Optional	Optional
Gas Hose (10ft.)	Optional	Optional
Installation Options:	Optional	Optional
Indoor Mount	Yes	Yes
Outdoor Mount	No	No
CSA U.S.A. Certified	Base/Standard versions are U.S.A. certified. -3 and -4 models are not.**	
CSA Canada Certified	Yes, All Models	No

* Tri-shield coating consists of three unique protective layers including: a non-corrosive hot-dipped galvanized steel, an oven-cured epoxy primer and a baked, thermosetting polyester.

** Base/Standard versions ship with t-stat, hose, regulator, and chain kit. Classic 60(N) base/standard versions also ship with piping hardware. -3 versions ship with chain kit only. -4 versions ship with t-stat and chain kit.



Innovative Heating Solutions

411 Mason Street, Onalaska, WI 54650
 800 345 7200 (toll free) or 608 783 5691
 608 783 6115 (fax)
info@lbwhite.com | www.lbwhite.com

Your L.B. White Dealer:

CA RESIDENTS:
 **WARNING**
 Cancer and reproductive harm. See
www.P65Warnings.ca.gov.



© 2017 L.B. White Company
 All rights reserved.

All specifications are subject
 to change without notice.

21013-C, 24161, 28852, 24207, 23418
 10Apr17