

PREMIER®	40
BTU/H RATING	40,000
FUEL TYPE	LP
FUEL SUPPLY	✓ RUN ON 20 LB. LP TANK*
FUEL CONSUMPTION LP GAS MAX	1.86 LBS./HR
ELECTRICAL SUPPLY	120 VOLTS / 60 HZ / 1 PHASE
AMP DRAW (STARTING/CONTINUOUS)	2.6 / 1.0
HEATED AIR OUTPUT (CFM)	330
MOTOR HORSEPOWER	1/12 HP
LENGTH	24.8"
WIDTH	14.5" **
HEIGHT	16.2"
UNIT WEIGHT	53 LBS
EST. SHIPPING WEIGHT	60 LBS
DUCTABLE	✓ YES, 8" DIA. X 12' LENGTH MAX
VENTILATION MODE (FAN ONLY)	✓ YES
DIAGNOSTIC LIGHTS	✓ YES
THIRD-PARTY CERTIFIED FOR SAFETY	✓ YES, FOR USE IN US AND CAN
RATED FOR INDOOR OR OUTDOOR USE	✓ YES
TWO YEAR WARRANTY	✓ YES
SHIPS WITH:	REGULATOR HOSE (3/8" DIA. X 15' LENGTH) THERMOSTAT (SINGLE STAGE NEMA 4 X 25" CORD)
OPTIONAL ACCESSORIES:	8" X 12' DUCT (REQUIRES LBW ADAPTER)
* AT 20°F AND 60% FULL	

AT 20 F AND 60% FULL

** 18.1" WITH THERMOSTAT BRACKET



CA RESIDENTS:

WARNING

Cancer and reproductive harm. See www.P65Warnings.ca.gov.









Smallest enclosed flame portable heater on the market!

- Runs on a single 20 lbs cylinder
- Ductable
- Ouiet
- Safe, enclosed flame
- Easy to operate with diagnostic lights
- Remote thermostat option

- Air circulation mode moves air even when heat is not needed
- Heavy Duty
 - Easy-grip handle
 - Tri-shield[™] coated case
 - Robust legs



Runs on a single 20 lbs cylinder



Ductable



Quiet



Safe, enclosed flame

