

NEW &
ENHANCED

FOREMAN® 500/750 2.0

Indirect-Fired Portable Heater

L.B.WHITE®

- ✓ **Reliable BTU** at 500,000 or 750,000 btu/hr
- ✓ **Reliable CFM** with two 12" dia. outlet
- ✓ Foreman 750 is **the lightest weight in its class and only one-person portable 750,000 btu/hr indirect-fired heater on the market**
- ✓ **Quiet operation** at 70 dB or less
- ✓ **Operator-friendly control panel** with:
 - Voltmeter that monitors incoming volts
 - Hour meter that clocks actual runtime (heat mode only)
 - Status and diagnostic lights

NEW **Ease of servicing - no belt to maintain**

NEW **More maneuverable**

- Reduction in length
- Reduction in weight

NEW **Foreman 750 now 120v**

- ✓ **Loaded with options to aid fuel efficiency** including thermostatic control, recirculation mode, and fan-only vent mode
- ✓ **60-gal. fuel tank** (operates as a backup tank on the Foreman 750)
- ✓ **Remote tank connection** that allows for quick switch to backup fuel tank (standard with Foreman 750, optional with Foreman 500)
- ✓ **Jobsite tough** with indoor/outdoor rating, robust parts and protective frame
- ✓ **Efficient storage options** with no flat wheels and frame that allows for vertical stacking

L.B.WHITE
LINK

L.B. White LINK™

Now telematics-enabled to put critical alerts, runtime, location, and more at your fingertips.

Learn more at LBWhite.com/LINK.

Accessories (Sold Separately)

Vent Pipe Extension
Rain Cap
Regulator for DF model only
Gas Hose for DF model only
Duct (12", 16" and/or 20" dia.)
Duct Adapter (Takes 2 x 12" down to 1 x 16")
Thermostat with 25 ft cord
Beckett® GeniSys Contractor Display Tool (For oil model only)
Stacking Kit



Control Panel:

- Volt Meter
- Hour Meter
- Diagnostic Lights



Easy access rear panel for maintenance and air recirculation option; just add 20" duct



Stackable (kit sold separately)



One-person portability



Powder-coated protective frame

Single point lifting bale

Thermostatic control option



Two 12" dia. duct up to 100 ft.



One 16" dia. duct up to 100 ft. using duct adapter (sold separately)

Fork pockets



**NEW &
ENHANCED**

FOREMAN® 500/750 2.0

Indirect-Fired Portable Heater

L.B.WHITE

FOREMAN®		500 DF	500 OIL	750 DF	750 OIL
BTU/H RATING		500,000	500,000	750,000	750,000
FUEL TYPE		LP, NG	#1 OR #2 DIESEL	LP, NG	#1 OR #2 DIESEL
FUEL CONSUMPTION MAX	LP (LBS./HR)	23.0	--	34.4	--
	NG (CU.FT./HR)	500.0	--	750.0	--
	DIESEL 1 OR 2 (G/HR)	--	3.6	--	5.4
INLET GAS PRESSURE MIN./MAX.	LP (IN W.C.)	8/13.5	--	8/13.5	--
	NG (IN W.C.)	8/13.5	--	8/13.5	--
BURNER TYPE		RIELLO®	BECKETT®	RIELLO®	BECKETT®
TANK CAPACITY (GALLON)		--	60	--	60
HEATED AIR OUTPUT (CFM)		2,350	2,350	3,364	3,364
BLOWER FAN (CFM)		3,457	3,457	4,280	4,280
OUTLET STATIC PRESSURE (IN W.C.)		2.5	2.5	2.5	2.5
OUTLET DUCT DIAMETER (INCH)		12X2	12X2	12X2	12X2
RECIRCULATION DUCT DIAMETER (INCH)		20	20	20	20
MOTOR HORSEPOWER		1.0	1.0	1.0	1.0
ELECTRICAL SUPPLY (VOLTS/HZ/PHASE)		120/60/1	120/60/1	120/60/1	120/60/1
AMPS (START/CONTINUOUS)		60/15	60/16	60/15	60/17
UNIT WEIGHT (LBS)		617	700	617	700
UNIT LENGTH (IN)		84.4	84.4	84.4	84.4
UNIT WIDTH (IN)		32.0	32.0	32.0	32.0
UNIT HEIGHT (IN)		52.5	52.5	52.5	52.5
SHIP WEIGHT (LBS)*		785	865	785	865
SHIP LENGTH (IN)		88	88	88	88
SHIP WIDTH (IN)		39	39	39	39
SHIP HEIGHT (IN)		60	60	60	60
TIGERLOOP OIL DE-AERATOR		--	0	--	S
LINK™ OPTION		0	0	0	0
THIRD PARTY CERTIFIED TO ANSI Z83.7/CSA 2.14-2017		YES	YES	YES	YES
TWO YEAR WARRANTY					

S=Standard O=Optional

*Ships on custom pallet.

Heaters ship standard to run at 0-2000 feet.
To operate at higher altitudes, please note in order
process to allow for appropriate deviation.



CA RESIDENTS:



WARNING
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE

info@jmesales.com E-MAIL
www.JMEsales.com WEB