

VOLT®

Electric Forced Air Portable Heaters

CONVENIENT, CLEAN HEAT



- ✓ User-friendly electric design
- ✓ For areas where heating & drying is needed
- ✓ Capable of quick, high temp rises
- ✓ Ventilation & air circulation are not needed

Jobsite Tough

- Industrial-grade fan
- Stainless jacketed heating coils
- Powder coated steel housing
- High-quality sealed motor

Safe & Reliable

- Quiet, combustion-free operation
- No fuel spills or odors
- Overheat protection at 104° F
- UL approved



Integrated ambient thermostat
from 32°F - 100°F



A John M. Ellsworth Company

John M. Ellsworth Co., Inc.





P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE

info@jmesales.com E-MAIL
www.JMESales.com WEB

VOLT[®] Electric Forced Air Portable Heaters



VOLT [®]	1.5	3	6	9	18-1	18-3	40	60
Wattage	1,500	3,000	6,000	9,000 (9kW) 6,000 (6kW)	19,000 (19kW) 13,000 (13kW)	19,000 (19kW) 13,000 (13kW)	40,000 (40kW) 32,000 (32kW) 16,000 (16kW)	60,000 (60kW) 48,000 (48kW) 24,000 (24kW)
BTU/H Rating	5,100	10,200	20,500	30,700 (9kW) 20,500 (6kW)	65,000 (19kW) 45,000 (13kW)	65,000 (19kW) 45,000 (13kW)	136,500 (40kW) 102,400 (32kW) 51,200 (16kW)	205,000 (60kW) 164,000 (48kW) 82,000 (24kW)
Electric supply (volts/hz/phase)	120/60/1	240/60/1	240/60/1	240/60/1	240 or 208*/60/1	240 or 208*/60/3	480/60/3	480/60/3
Amps (Starting/ Continuous Operation)	12.5	12.5	25	37.5 (9kW) 25 (6kW)	81 (19kW) 54 (13kW)	47 (19kW) 31 (13kW)	50 (40kW) 40 (32kW) 20 (16kW)	75 (60kW) 60 (48kW) 30 (24kW)
Blower Fan Output (CFM)	116	205	250	350	590 or 1,000	590 or 1,000	1,765	1,765
Power Cord	10ft, 12AWG	10ft, 16AWG	10ft, 8AWG	10ft, 8AWG	Not included	Not included	Not included	Not included
Max Cable Length	N/A	N/A	100-ft (8AWG, 3-wire, SOOW)	50-ft (8AWG, 3-wire, SOOW) 100-ft (6AWG, 3-wire, SOOW)	50-ft (2AWG, 3-wire, SOOW)	50-ft (6AWG, 4-wire, SOOW) 100-ft (4AWG, 4-wire, SOOW)	50-ft (4AWG, 4-wire, SOOW) 100-ft (2AWG, 4-wire, SOOW)	50-ft (2AWG, 4-wire, SOOW)
Plug	NEMA 5-15P 	NEMA 6-15P 	NEMA 14-30P 	NEMA 14-50P 	Not included	Not included	Not included	Not included
Ambient Thermostat Temperature Range	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F	32 - 100 °F
Length (in.)	11	11	20	23	32	32	46	46
Width (in.)	12	10	12	14	14.5	14.5	20	20
Height (in.)	8	15	17	18	20.5	20.5	25	25
Unit Weight (lbs.)	13.7	20.3	32.9	39.9	62	62	125	125
Shipping Weight (lbs.)	15	22	40	42	65	65	130	130
Running Decibels (dba)	47	50	55	55	58	58	82	82
Three Heat Output Modes	-	-	-	-	S	S	S	S
Powder Coated Steel Housing	S	S	S	S	S	S	S	S
Wheels	-	-	-	-	-	-	S	S
UL Approved	S	S	S	S	S	S	S	-

S=Standard

* Does not operate at full output

CA RESIDENTS:

 **WARNING**
Cancer and reproductive harm. See
www.P65Warnings.ca.gov.

INNOVATIVE CLIMATE SOLUTIONS