

FIXED AUTOMATIC HOSE REELS IN PAINTED STEEL FOR OIL, ANTIFREEZE AND SIMILAR FLUIDS FROM 88 TO 160 bar

Equipped with:

- Black synthetic rubber hoses 1SC
- Galvanized steel connections
- Galvanized steel 90° swivelling joint
- Polyurethane seals



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE
info@jmesales.com E-MAIL
www.jmesales.com WEB

F-400	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1206-400	without hose	-	-	F1/2"G - M1/2"G
	070-1206-310	10 m	3/8"	180 bar	F1/2"G - M1/2"G
	070-1206-410	10 m	1/2"	160 bar	F1/2"G - M1/2"G

F-460	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1306-400	without hose	-	-	F1/2"G - M1/2"G
	070-1306-315	15 m	3/8"	180 bar	F1/2"G - M1/2"G
	070-1306-415	15 m	1/2"	160 bar	F1/2"G - M1/2"G
	070-1306-418	18 m	1/2"	160 bar	F1/2"G - M1/2"G

F-550	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1406-400	without hose	-	-	F1/2"G - M1/2"G
	070-1406-500	without hose	-	-	F1"G - M3/4"G
	070-1406-420	20 m	1/2"	160 bar	F1/2"G - M1/2"G
	070-1406-425	25 m	1/2"	160 bar	F1/2"G - M1/2"G
	070-1406-515	15 m	3/4"	105 bar	F1"G - M3/4"G

F-555	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1506-400	without hose	-	-	F1/2"G - M1/2"G
	070-1506-500	without hose	-	-	F1"G - M3/4"G
	070-1506-600	without hose	-	-	F1"G - M1"G
	070-1506-430	30 m	1/2"	160 bar	F1/2"G - M1/2"G
	070-1506-520	20 m	3/4"	105 bar	F1"G - M3/4"G
	070-1506-615	15 m	1"	88 bar	F1"G - M1"G

F-560	Article	L. hose	Ø hose	Max pressure	Inlet-Outlet
	070-1606-400	without hose	-	-	F1/2"G - M1/2"G
	070-1606-500	without hose	-	-	F1"G - M3/4"G
	070-1606-600	without hose	-	-	F1"G - M3/4"G
	070-1606-440	40 m	1/2"	160 bar	F1"G - M3/4"G
	070-1606-525	25 m	3/4"	105 bar	F1"G - M3/4"G
	070-1606-530	30 m	3/4"	105 bar	F1"G - M3/4"G
	070-1606-620	20 m	1"	88 bar	F1"G - M1"G
	070-1606-630	30 m	1"	88 bar	F1"G - M1"G

OVERALL DIMENSIONS FIXED VERSION

Mod.	A	B	C	D	E	F	G	H			
F-400	158	120	168	192	95	460	400	435	12,50<19,50	0,084	1
F-460	158	120	168	192	95	490	460	490	16,50<23,00	0,094	1
F-550	200	150	225	270	120	590	550	600	22,00<45,00	0,130	1
F-555	250	200	225	270	170	590	550	600	26,00<53,00	0,150	1
F-560	440	390	225	270	360	590	550	600	33,00<83,00	0,240	1

