

Rigid polyethylene tank for DEF-AdBlue® transport for non-commercial use, with built-in transfer unit consisting of rotary vane self-priming pump available in various voltages (12-24V). Delivery hose ø 19 mm 4 m length and automatic nozzle. The system is available at 220 liters and can be integrated with digital flow meter. The tank is equipped with 2" filling plug with pressurizing/depressurizing relief valve. See ADR Regulations at page 180.

"DEF-AdBlue® Tank 220" series composed by:



Art. 097-6220-000 Tank 220 l without pumps



Art. 098-6500-012 Electric diaphragm pump for DEF-AdBlue® 12V 34 l/min
cable 4 m length with pincers

Art. 098-6500-024 Electric diaphragm pump for DEF-AdBlue® 24V 34 l/min
cable 4 m length with pincers



Art. 099-5124-000 Digital flow meter MEC 24 min-max flow rate 5-120 l/min.



Art. 921-0500-040 Antistatic hose EPDM 20 bar G 3/4" 4 m length (19x27)



Art. 099-5210-000 Automatic stainless steel nozzle "AD80" Flow rate 80 l/min



Ref.	Descrip.	Flow meter	Voltage	Power	Inlet-outlet	Conn. hose	Nozzle	Cable L.mt	Flow meter	Weight	Packaging
		l/min	DC Volt	W	BSPG	Ø				kg	mm

097-6220-012	Tank 220 I	34	12	180	3/4"-3/4"	19x27	Aut.AD80	4	NO	37,00	910X600X620
097-6221-012	Tank 220 I	34	12	180	3/4"-3/4"	19x27	Aut.AD80	4	YES	37,35	910X600X620

097-6220-024	Tank 220 I	34	24	180	3/4"-3/4"	19x27	Aut.AD80	4	NO	37,00	910X600X620
097-6221-024	Tank 220 I	34	24	180	3/4"-3/4"	19x27	Aut.AD80	4	YES	37,35	910X600X620

PUMP DUTY CYCLE min: S2 20

