

# Model 515 Series AST Remote Spill Container

SPECIFICATION SHEET

For use on aboveground storage tanks for the purpose of containing fuel spillage during remote tank filling operations.

## Features

- Available in 2", 3" and 4" versions.
- 2" and 3" versions are ULC Listed
- Lid and container constructed of 12 Ga. (.105) steel
- 22½" wide x 24" deep—Container height 24½"
- 15 gallon capacity
- Powder coated white
- Weather-tight enclosure
- Container continuously vents to prevent buildup of vapors and internal pressure
- 1" NPT drain with locking ball valve
- Single column base—adjustable height 31"–47"
- Base plate with four ½" mounting holes. Custom order for a post hole mount or box only
- Lockable lid
- Container can hold up to two 2" or 3" Morrison swing check valves, ball valves, quick couplers and dust caps
- Choice of one or two fill ports in 2", 3" or a combination
- 2" bung for pump
- Gasspring cylinder holds lid open during use
- A top connection Figure 515OEM without a pedestal is also available. ***This is not ULC Listed.***

## Code Compliance

- Florida DEP EQ535
- Meets the new and revised requirements for CAN-ULC-S663-11 (effective September 25, 2015)



I.D Number	A	B	C	D	E	F	G	H
515--0200 AC	P	1	2"	B	Y	23	24	136.5
515--0300 AC	P	1	3"	B	Y	23	24	138
515--0400 AC	P	1	4"	B	Y	23	24	140
515--2200 AC	P	2	2" & 2"	B	Y	23	24	147
515--2300 AC	P	2	3" & 3"	B	N	23	24	150
515--3200 AC	P	2	2" & 3"	B	N	23	24	148.5
515OEM0200 AC	T	1	2"	T	N	23	24	103
515OEM0300 AC	T	1	3"	T	N	23	24	101
515OEM2200 AC	T	2	2" & 3"	T	N	23	24	107
515OEM2300 AC	T	2	3" & 3"	T	N	23	24	103

### SPECIFICATION OPTIONS:

- A**—Mounting Connection: Post Mount Female Thread (P)  
Back Mount 4 Tabs (T)  
**B**—Number of Ports  
**C**—Port Sizes, Female NPT  
**D**—Port Location, Back (B), Top (T)  
**E**—ULC Listed (Y), Not Listed (N)  
**F**—Width (Inches) (+/- ½")  
**G**—Height (Inches) (+/- ½")  
**H**—Shipping Weight (lbs)

