


Earth-Rite® II FIBC

Static Grounding Protection for Type C FIBCs



Earth-Rite II FIBC Type C Static Grounding System



Typical Earth-Rite II FIBC installation consisting of two grounding clamps that establish a continuous ground monitoring loop with the site's locally verified true earth ground source.

NFPA 77 "Recommended Practice on Static Electricity" highlights Flexible Intermediate Bulk Containers (FIBC) as being capable of accumulating electrostatic charge during product transfer operations.

NFPA 77 16.6.3 states "FIBCs should be tested in accordance with the requirements and test procedures specified in IEC 61340-4-4* and in accordance with their intended use before being used in hazardous environments."

NFPA 77 also states that Type C FIBC should be grounded during bag filling and emptying operations.

The Earth-Rite® II FIBC is a grounding system for Type C bags that are manufactured in accordance with IEC 61340-4-4. It consists of a grounding system and a pair of grounding clamps.

If the resistance through the conductive or static dissipative elements of the Type C bag is less than the required threshold, the ground status indicators switch from red to pulsing green.

It should be noted that the grounding system is not a substitute for the test methods outlined in IEC 61340-4-4. The grounding system indicates that the threshold resistance of the conductive dissipative / components of the bag are in line with the specified resistance range and that a ground loop has been established with the site's locally verified ground source.

The static dissipative performance of the bag is the sole responsibility of the bag manufacturer and the site owner.

*** Recommended upper monitoring resistance level:-**

- NFPA 77 Recommended Practice on Static Electricity, states that the resistance through a Type C FIBC bag should not exceed 1×10^8 Ohms (100 Meg Ohm).
- IEC 61340-4-4 Electrostatics – Part 4-4: Standard test methods for specific applications – Electrostatic classification of flexible intermediate bulk containers (FIBC), states that the resistance through a Type C FIBC bag should not exceed 1×10^8 Ohms (100 Meg Ohm).



The Earth-Rite II FIBC can be installed in Zoned / Classified combustible dust atmospheres. If gas and vapour atmospheres are present an Ex(d) / XP, Zone 1 / Class I, Div. 1 system may be specified.

The Earth-Rite II FIBC includes:

- Static Dissipative GRP Enclosure with Intrinsically Safe Monitoring Circuits.
- FIBC Grounding Clamp with single conductor Hytrel® Protected Cable.
- Junction Box with Stowage Pin for stowing FIBC Grounding Clamp.

Earth-Rite® II FIBC

Features

Continuous Ground Loop Monitoring

The grounding system clamp, which must be connected to the identified grounding tab on the bag, provides an intrinsically safe signal that returns to the grounding system via a locally verified ground source.

This circuit establishes a ground monitoring resistance loop so that when the resistance threshold is below (100 Meg Ohm) or (10 Meg Ohm) the grounding system will go permissive. When the permissive condition is met the ground status indicators switch from red to pulsing green. The most consistent method of achieving a ground return path is with a second grounding clamp supplied with the system. This must be connected to a separate identified grounding tab connection point, preferably to the opposite end of the bag to which the system grounding clamp is connected.

The locally verified and maintained/tested ground source must be verified by the site owner/responsible as being connected to the general mass of the earth suitable to dissipate static charges. (Contact Newson Gale for further details).

Dry Contacts

Earth-Rite system output contacts can be interlocked with process equipment and/or strobes. Interlocking the grounding system with the process equipment can enhance the Standard Operating Procedures (SOP) before the movement of material can take place. Interlocking with strobes provides personnel with a wider field of view that the grounding SOP is underway.

On rare occasions grounding clamps can be removed by operators or lose contact with equipment due to unstable connections being made initially or overstretching of the cable connected to the grounding clamp. The grounding system can, via the output contacts, halt the process. However, please be aware that the movement of the product may not stop even though the equipment has halted. This could lead to the continued generation of static charge. In such circumstances it is the responsibility of the site operator to ensure their SOPs cater for such scenarios. This assumes the grounding system has been installed in accordance with the Instruction Manual. If you do not have access to an Instruction Manual contact Newson Gale.

Loading Operations:

Varying cable lengths are available to attach the clamp to the FIBC bag. However, if the bag loading / unloading process is aggressive and could cause the grounding clamp connection to be compromised irrespective of cable length, an alternative means of grounding the bag will need to be sourced.



Earth-Rite II FIBC stainless steel grounding clamp
with Quick Connect and optional lengths of Hytrel protected
single core cable included



Earth-Rite® II FIBC

Static Grounding Protection for Type C FIBCs

Earth-Rite® II FIBC

Technical Specification

GRP (Class I, II, III - Div. 2 Installations)

Power Supply & Monitoring-Unit

Power Supply	115 V or 230 V AC, 50-60 Hz 12 V or 24 V DC
Power Rating	10 watt
Ambient Temperature Range	-13°F to +131°F
Ingress Protection	Type 4X (IP 66)
Weight	3.3 lbs (1.5 Kg) nett
Construction	Carbon-Loaded GRP
Monitoring Circuit	Intrinsically safe
Operational Monitoring Resistance of Bag	Nominally $\leq 1 \times 10^8$ or $1 \times 10^7 \Omega$ ($\pm 10\%$)
Output Relay Contact Rating	2 off change-over dry contacts, 250 V AC, 5 A, 500 VA max resistive, 30 V DC, 2 A, 60 W max resistive
Cable Entries	7 x M20 (2 x plugged)

Junction Box/Stowage Point

Enclosure Material	GRP with carbon loading
Terminals	2 x AWG #14 conductor capacity
Stowage Device	Insulated universal stowage pin
Cable Entries	1 x M20
Clamp Cable Connection	Quick Connect

Grounding Clamp

Clamp Design	1 pole with single stainless steel contact
Body	Stainless Steel (SS grade: 304)

ATEX / IECEx / UKEX Certification:

UKCA Ex

Ex II 1 G
Ex II 1 D

Ex h IIC T6 Ga

Ex h IIIC T85°C Da

Ta = -40°C to +60°C

ExVeritas 21UKEX0842

UKCA Ex Approved Body: ExVeritas

ATEX

Ex II 1 GD T6

(Assessed to EN 13463-1 : 2009)

Ta = -40°C to +60°C

Sira 02ATEX9381

ATEX Notified Body: SIRA

IECEx

Ex h IIC T6 Ga

Ex h IIIC T85°C Da



Ta = -40°C to +60°C

IECEx EXV 20.0033


IECEx Certified Body: ExVeritas

Spiral Cable

Cable	Blue Cen-Stat Hytrel sheath (Static dissipative, chemical & abrasion resistant)
Conductors	1 x AWG #12 steel
Length	3 m (10 ft), 5 m (16 ft), 10 m (32 ft) or 15 m (50 ft) Cen-Stat blue spiral cable with Hytrel coating which has colour, UV protective and static dissipative additives



Simple Apparatus
GRP junction box with nylon grounding clamp stowage pin



Earth-Rite® II FIBC

GRP Hazardous Location Approvals

North America:

NEC 500 / CEC (Class & Division)

Associated Equipment [Ex ia] for use in
Class I, Div. 2, Groups A, B, C, D
Class II, Div. 2, Groups E, F, G
Class III, Div. 2
Providing Intrinsically Safe circuits for
Class I, Div. 1, Groups A, B, C, D
Class II, Div. 1, Groups E, F, G
Class III, Div. 1
Temperature Code T4
Ta = -13°F to +131°F
OSHA recognised NRTL: CSA

NEC 505 & 506 (Class & Zoning)

Class I, Zone 2, (Zone 0), AEx nA[ia] IIC T4
Class II, Zone 21, AEx tD[iaD] 21, T70°C

CEC Section 18 (Class & Zoning)


Class I, Zone 2 (Zone 0) Ex nA[ia] IIC T4
DIP A21, IP66, T70°C

Europe / International: Version Available


IECEx

Ex ec nC [ia Ga] IIC T4 Gc
Ex tb [ia Da] IIIC T70°C Db
Ta = -40°C to +55°C
IECEx EXV 19.0059X
IECEx Certifying Body: ExVeritas

ATEX

 II 3(1)G
II 2(1)D
Ex ec nC [ia Ga] IIC T4 Gc
Ex tb [ia Da] IIIC T70°C Db
Ta = -40°C to +55°C
ExVeritas 19ATEX0545X
ATEX Notified Body: ExVeritas

UKCA Ex

 II 3(1)G
II 2(1)D
Ex ec nC [ia Ga] IIC T4 Gc
Ex tb [ia Da] IIIC T70°C Db
Ta = -40°C to +55°C
ExVeritas 21UKEX0833X
UKCA Ex Approved Body: ExVeritas

CCC

Ex ec [ia Ga] nC IIC T4 Gc
Ex tb [ia Da] IIIC T70°C Db
2021312304001041
Approved Body: CNEX

KCS (Gas)

Ex ec nC [ia Ga] IIC T4 Gc(Ga)
Ta = -40°C to +55°C
22-AV4BO-0319X
Approved Body: KOSHA

KCS (Dust)

Ex tb IIIC T70°C Db
Ta = -40°C to +55°C
22-AV4BO-0320X
Approved Body: KOSHA

Additional Certification

Safety Integrity Level:

SIL 2 (in accordance with IEC/EN 61508)

EMC Tested:

to EN 61000-6-3, EN 61000-6-2
FCC - Part 15 (Class B)

Earth-Rite® II FIBC

Static Grounding Protection for Type C FIBCs

Earth-Rite® II FIBC

Technical Specification

XP (Class I, II, III - Div. 1 Installations)

Monitoring unit

Power Supply	115 V or 230 V AC, 50-60 Hz 12 V or 24 V DC
Power Rating	10 watt
Ambient Temperature Range	-40°F to +122°F
Ingress Protection	Type 4X (IP 66)
Weight	9.9 lbs (4.5 kg) nett
Construction	Copper-free cast aluminium
Monitoring Circuit	Intrinsically safe
Operational Monitoring Resistance of Bag	Nominally $\leq 1 \times 10^8$ or $1 \times 10^7 \Omega$ ($\pm 10\%$)
Output Relay Contact Rating	2 off change-over dry contacts, 250 V AC, 5 A, 500 VA max resistive 30 V DC, 2 A, 60 W max resistive
Cable Entries	7 x 3/4" NPT (supplied with 4 stopper plugs)

Junction Box/Stowage Point

Enclosure Material	GRP with carbon loading
Terminals	2 x AWG #14 conductor capacity
Stowage Device	Insulated universal stowage pin
Cable Entries	1 x M20
Clamp Cable Connection	Quick Connect

Grounding Clamp

Clamp Design	1 pole with single stainless steel contact
Body	Stainless Steel (SS grade: 304)

ATEX / IECEx / UKEX Certification:

UKCA Ex

Ex h IIC T6 Ga
Ex h IIIC T85°C Da
Ta = -40°C to +60°C
ExVeritas 21UKEX0842
UKCA Ex Approved Body: ExVeritas

ATEX




II 1 GD T6
(Assessed to EN 13463-1 : 2009)
Ta = -40°C to +60°C
Sira 02ATEX9381
ATEX Notified Body: SIRA

IECEx

Ex h IIC T6 Ga
Ex h IIIC T85°C Da
Ta = -40°C to +60°C
IECEx EXV 20.0033
IECEx Certified Body: ExVeritas

Spiral Cable

Cable	Blue Cen-Stat Hytrel sheath (Static dissipative, chemical & abrasion resistant)
Conductors	1 x AWG #12 steel
Length	3 m (10 ft), 5 m (16 ft), 10 m (32 ft) or 15 m (50 ft) Cen-Stat blue spiral cable with Hytrel coating which has colour, UV protective and static dissipative additives



Simple Apparatus
GRP junction box with nylon grounding clamp stowage pin

Earth-Rite® II FIBC

XP/Exd Hazardous Location Approv-

North America:

NEC 500 / CEC (Class & Division)

Associated Equipment [Ex ia] for use in
Class I, Div. 1, Groups A, B, C, D
Class II, Div. 1, Groups E, F, G
Class III, Div. 1
Providing intrinsically safe circuits for
Class I, Div. 1, Groups A, B, C, D
Class II, Div. 1, Groups E, F, G
Class III, Div. 1
Temperature Code T6
Ta = -40°F to +122°F
OSHA recognised NRTL: CSA.

NEC 505 & 506 (Class & Zoning)

Class I, Zone 1 [0] AEx d[ia] IIC T6 Gb(Ga)
Class II, Zone 21 [20] AEx tD [iaD] 21 T80°C

CEC Section 18 (Class & Zoning)


Class I, Zone 1 [0] Ex d[ia] IIC T6 Gb(Ga)
DIP A21, IP66, T80°C

Europe / International: Version Available


IECEX

Ex db [ia Ga] IIC T6 Gb
Ex tb [ia Da] IIIC T80°C Db
Ta = -40°C to +55°C
IECEX EXV 19.0052
IECEX Certifying Body: ExVeritas

ATEX

 II 2(1)G
II 2(1)D
Ex db [ia Ga] IIC T6 Gb
Ex tb [ia Da] IIIC T80°C Db
Ta = -40°C to +55°C
ExVeritas 19ATEX0537
ATEX Notified Body: ExVeritas

UKCA Ex

 II 2(1)G
II 2(1)D
Ex db [ia Ga] IIC T6 Gb
Ex tb [ia Da] IIIC T80°C Db
Ta = -40°C to +55°C
ExVeritas 21UKEX0832
UKCA Ex Approved Body: ExVeritas

CCC

Ex db [ia Ga] IIC T6 Gb
Ex tb [ia Da] IIIC T80°C Db
2021312304001040
Approved Body: CNEX

KCS (Gas)

Ex d [ia Ga] IIC T6 Gb(Ga)
Ta = -40°C to +55°C
22-AV4BO-0334X
Approved Body: KOSHA

KCS (Dust)

Ex tb IIIC T80°C IP66 Db
Ta = -40°C to +55°C
22-AV4BO-0335X
Approved Body: KOSHA

Additional Certification

Safety Integrity Level:

SIL 2 (in accordance with IEC/EN 61508)

EMC Tested:

to EN 61000-6-3, EN 61000-6-2
FCC - Part 15 (Class B)

System Options

Universal Resistance Tester (URT)

The URT is designed to provide users of Newson Gale **Earth-Rite®** static grounding systems with a means of testing the permissive resistance range on a regular basis.


The easy to use tester consists of a pair of rotary switches that enable a competent electrical person to check the resistance level at which the grounding system should be working and conduct a PASS / FAIL test at the required setting.



Intrinsically Safe (I.S) Switching PCB

The I.S Switching PCB is an additional circuit board added to Newson Gale system enclosures to enable users to directly interface with, and switch intrinsically safe circuits without the need for additional equipment. The I.S Switching PCB is designed not to affect the I.S signals electrical parameters and is compatible with the Earth-Rite II FIBC platforms.

- 30 V DC, 500 mA
- Li = 0H, Ci = 0F
- Suitable for Ex ia, ib, ic rated intrinsically safe circuits only
- NAMUR Compatible



Copyright Notice

The website and its content is copyright of Newson Gale Ltd © 2020. All rights reserved.

Any redistribution or reproduction of part or all of the contents in any form is prohibited other than the following:

- you may print or download to a local hard disk extracts for your personal and noncommercial use only
- you may copy the content to individual third parties for their personal use, but only if you acknowledge the website as the source of the material

You may not, except with our express written permission, distribute or commercially exploit the content. Nor may you transmit it or store it in any other website or other form of electronic retrieval system.

Right to change

This document provides general information only and may be subject to change at any time without notice. All information, representations, links or other messages may be changed by Newson Gale at any time without prior notice or explanation.

Newson Gale is not obliged to remove any outdated information from its content or to expressly mark it as being outdated. Please seek the advice of professionals as necessary regarding the evaluation of any content.

Disclaimer of liability

The information provided in this Datasheet is provided by Newson Gale without any representations or warranties, expressed or implied, as to its accuracy or completeness. The liability of Newson Gale for any expenses, losses or actions incurred whatsoever by the recipient as a result of the use of this Datasheet shall be excluded.