
AUTOMATIC INFLATORS MINI TIRE INFLATORS



— ACCURA® QUBE

SPECIFICATIONS

Compliance:	EC Directive 86/217 and BS EN 12645:1999
Reading Accuracy:	1 psi
Max. Supply Pressi	ire: 217 psi
Inflation Flow:	88 cfm
Inflation Range:	0-145 psi
Operating Tempera	ture: -4°F to 158°F
Dimensions:	6" x 6" x 4"



ACCURA® QUBE MINI TIRE INFLATOR

PCL offers cost-effective & accurate tire inflation boxed off with this space-saving, entry-level unit, the ACCURA® QUBE Tire Inflator.

PCL proves that being square can be stylish with its simplest electronic tire inflator to date, the user-friendly ACCURA $^{\circ}$ QUBE Tire Inflator. This tiny 6" x 6" unit packs a petite, yet powerful punch, offering fast and accurate tire inflation within a simple, safe, state-of-the-art design.

The QUBE is just as reliable and straightforward as all products in PCL's leading ACCURA® range of preset inflators, yet features just three modes: standard inflate/deflate, tire shop (featuring overpressure) and nitrogen (top off and complete purge). All the customer needs to do is preset the required pressure, place the connector on the tire, and let the built-in auto-start function do the rest.

In short, the QUBE is designed to be simple and space-saving, without the programming or customization of the more expensive models. This versatile little unit is ideal for indoor use, particularly in commercial environments where ease of use and accuracy are key.

KEY BENEFITS

Plug and play - with 3 pre-selectable application MODES:

MODE 1 - Standard inflate/deflate

MODE 2 - Tire shop with over-pressure

MODE 3 - N2 fill and AIR to N2 conversion

Low and simple maintenance

Individually tested calibration certificate included

Touch Capacitive technology

Electronic pressure preset

Auto-start inflation

Clear display for easy readability

Ceramic sensor - accuracy to +/- 0.5 of full scale reading

Accurately inflates using hoses up to 164 ft. in length

Comprehensive diagnostics and error reporting

Low lifetime costs with proven electronics

Can be easily wall-mounted (indoor use only)

PART #	DESCRIPTION
QUBE 4	INCLUDES 16' HOSE WITH SINGLE LOCK-ON CHUCKS, 110V
QUBE 44x25	INCLUDES FOUR 25' HOSES, SINGLE LOCK-ON CHUCKS, 110V
QUBE 6	QUBE 12V, NO HOSES
QUBE 6HC	QUBE 12V, 25' HOSE, SINGLE LOCK-ON CHUCK

