

CHJ060A





Battery (2.0 Ah), Charger and DCB092 USB Power Adapter

OUTER SHELL - Polyester Soft Shell / INNER SHELL - Polyester

Sizes: S, M, L, XL, 2X, 3X

Insulated woven outer shell

Warm fleece polyester lining

Smooth finish polyester sleeve lining for easy on/off

Adjustable hook & loop cuffs and waist draw-cord to customize fit and block wind and wet

2 zipper slash pockets, 1 external zipper accessory pocket, 1 internal zipper accessory pocket, and 1 internal accessory pocket with hook & loop closure

Front zipper with internal wind guard

Low funnel neck with chin guard



DELUXE KIT (D1) Includes: DCHJ060A Heated Jacket, DCB203 20V MAX* Lithium-lon DCHJ060AB (BLACK)

BASIC KIT (B)

Includes: DCHJ060A Heated Jacket, DCB092 USB Power Adapter











With respect to 20V MAX, maximum initial battery voltage (measured without a workload) is 20 volts. Nominal voltage is 18. *With respect to 12V MAX*, maximum initial battery voltage (measured without a workload) is 12 volts. Nominal voltage is 10.8.

**Actual run time varies depending on battery type and heat setting

Copyright ©2018 DEWALT. DEWALT is a registered trademark of DEWALT Industrial Tool Co., used under license. All rights reserved. The yellow and black color scheme is a trademark for DEWALT Power Tools and Accessories. Trademark License: Radians, Inc., Memphis, TN 38141, 877-723-4267, www.radians.com. A licensee of DeWALT Industrial Tool Co.

GUARANTEED TOUGH:

