

E

Drive Type

A - Air motor
B - Bevel crank
C - Hand crank
E - Electric motor

A 3 3

Swivel Size

2 - 1/2" (13 mm) I.D.
3 - 3/4" (19 mm) I.D.
6 - 1/4" (6 mm) Dual
7 - 1" (25 mm) I.D.
8 - 1/2" (13 mm) I.D. pressure wash

1 06

Width of Spool

See "F" Dimension
06 - 6" (152 mm)
12 - 12" (305 mm)
18 - 18" (457 mm)

L 12D

Motor Voltage/H.P.

Blank
12D - 12 V DC
4A - 1 1/2 HP air motor

Fluid Path Type



A - Gooseneck
H - Heavy duty gooseneck (1" only)

Pressure

L - 1000 PSI (69 bar)
M - 3000 PSI (207 bar)

NOTE: Chart is for reference only. Not all options available in every combination. Reels cannot be ordered by selecting from this chart.

Hose I.D.	1/4"	3/8"	1/2"	3/4"	1"
	6 mm	10 mm	13 mm	19 mm	25 mm
Hose O.D.	.530"	.710"	.850"	1.188"	1.375"
	13 mm	18 mm	22 mm	30 mm	35 mm
"F" Width	Hose Capacity				
6"	200'	140'	100'	50'	N/A
152 mm	61 m	43 m	30 m	15 m	
12"	425'	300'	200'	100'	50'
305 mm	130 m	91 m	61 m	30 m	15 m
18"	625'	450'	325'	175'	100'
457 mm	191 m	137 m	99 m	54 m	31 m

Additional Series 30000 Models

Pressure Wash - Page 22 Welding Gas - Page 33
Hose Reel Cart - Page 23

Models with a ★ icon are our most popular models.

Model without hose & bumper	Shipping Weight		Hose Capacity						Max Pressure		NPT(F) Reel Inlet	NPT(F) Reel Outlet	D		E		F		G	
			I.D.		O.D.		Length													
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in	in	mm	in	mm	in	mm	in	mm
Manual Hand Crank Hose Reels Maximum Temperature 210 °F (99 °C)																				
CA32106 L	40	18	1/2	13	.750	19	100	30	100	69	1/2	1/2	9 ³ / ₄	248	19 ³ / ₄	502	6	152	6 ³ / ₈	162
CA32112 L ★	46	21	1/2	13	.750	19	200	61	1000	69	1/2	1/2	15 ³ / ₄	400	25 ³ / ₄	654	12	305	6 ³ / ₈	162
CA32118 L	51	23	1/2	13	.750	19	325	99	1000	69	1/2	1/2	21 ³ / ₄	552	31 ³ / ₄	806	18	457	6 ³ / ₈	162
CA32106 M	42	19	1/2	13	.850	22	100	30	3000	207	1/2	1/2	9 ³ / ₄	248	19 ³ / ₄	502	6	152	6 ³ / ₈	162
CA32112 M	46	21	1/2	13	.850	22	200	61	3000	207	1/2	1/2	15 ³ / ₄	400	25 ³ / ₄	654	12	305	6 ³ / ₈	162
CA32118 M	52	24	1/2	13	.850	22	325	99	3000	207	1/2	1/2	21 ³ / ₄	552	31 ³ / ₄	806	18	457	6 ³ / ₈	162
CA33106 L	41	19	3/4	19	1.075	27	50	15	1000	69	3/4	3/4	9 ³ / ₄	248	19 ³ / ₄	502	6	152	6 ³ / ₈	162
CA33112 L ★	46	21	3/4	19	1.075	27	100	30	1000	69	3/4	3/4	15 ³ / ₄	400	25 ³ / ₄	654	12	305	6 ³ / ₈	162
CA33118 L	51	23	3/4	19	1.075	27	175	53	1000	69	3/4	3/4	21 ³ / ₄	552	31 ³ / ₄	806	18	457	6 ³ / ₈	162
CA33112 M	47	21	3/4	19	1.188	30	100	30	3000	207	3/4	3/4	15 ³ / ₄	400	25 ³ / ₄	654	12	305	6 ³ / ₈	162
CA33118 M	51	23	3/4	19	1.188	30	175	53	3000	207	3/4	3/4	21 ³ / ₄	552	31 ³ / ₄	806	18	457	6 ³ / ₈	162
CH37112 L*	60	27	1	25	1.375	35	50	15	1000	69	1	1	15 ³ / ₄	400	25 ³ / ₄	654	12	305	8	203
CH37118 L*	64	29	1	25	1.375	35	100	30	1000	69	1	1	21 ³ / ₄	552	31 ³ / ₄	806	18	457	8	203
Electric Motor Driven Hose Reels Maximum Temperature 210 °F (99 °C)																				
EA32106 L12D	60	27	1/2	13	.750	19	100	30	1000	69	1/2	1/2	9 ³ / ₄	248	19 ⁵ / ₈	498	6	152	6 ³ / ₈	162
EA32112 L12D	64	29	1/2	13	.750	19	200	61	1000	69	1/2	1/2	15 ³ / ₄	400	23 ⁷ / ₈	606	12	305	6 ³ / ₈	162
EA32118 L12D	68	31	1/2	13	.750	19	325	99	1000	69	1/2	1/2	21 ³ / ₄	552	29 ⁵ / ₈	752	18	457	6 ³ / ₈	162
EA33106 L12D	63	29	3/4	19	1.075	27	50	15	1000	69	3/4	3/4	9 ³ / ₄	248	19 ⁵ / ₈	498	6	152	6 ³ / ₈	162
EA33112 L12D	68	31	3/4	19	1.075	27	100	30	1000	69	3/4	3/4	15 ³ / ₄	400	23 ⁷ / ₈	606	12	305	6 ³ / ₈	162
EA33118 L12D ★	68	31	3/4	19	1.075	27	175	53	1000	69	3/4	3/4	21 ³ / ₄	552	29 ⁵ / ₈	752	18	457	6 ³ / ₈	162
EH37118 L12D*	82	37	1	25	1.375	35	100	30	1000	69	1	1	21 ³ / ₄	552	31	787	18	457	8	203
Air Motor Driven Hose Reels Filter, regulator, lubricator required. Maximum Temperature 210 °F (99 °C)																				
AA32106 L4A	54	24	1/2	13	.750	19	100	30	1000	69	1/2	1/2	9 ³ / ₄	248	17 ¹ / ₄	438	6	152	6 ³ / ₈	162
CAUTION: To prevent drum damage fully extend and pressurize hose and rewind on the reel. *All 1 in. reel models have an 8 in. (203 mm) diameter drum.																				

CAUTION: To prevent drum damage fully extend and pressurize hose and rewind on the reel. *All 1 in. reel models have an 8 in. (203 mm) diameter drum.

Many more reel models available in addition to chart. Refer to reelcraft.com for details.



John M. Ellsworth Co., Inc.

P.O. Box 240072
8700 West Bradley Road
Milwaukee, WI 53224

800-333-3331 PHONE

info@jmesales.com E-MAIL
www.JMESales.com WEB