

Spring Retractable & Hand Crank Hose Reels

Air/Water - 1/2", 5/8", 3/4", 1" I.D.

Spring Retractable

- Models include outlet hose with brass on/off ball valve, bumper, and inlet hose providing a reel solution out of the box
- Comes equipped with garden hose end fittings
- Guide arm is easily adjustable to numerous positions
- All steel parts are individually powder-coated for maximum corrosion resistance
- Designed to be mounted centrally and used for watering and washdown
- Reel components are made from industrial grade steel

Hand Crank

- Ideal for longer lengths of hose and larger storage capacity
- All models include a 10 ft. inlet hose
- Designed to be mounted centrally and used for watering and washdown
- All steel parts are individually powder-coated for maximum corrosion resistance
- A 3/4 in. garden hose adapter for the outlet hose is included (except GCCB37118 L)
- Reel components are made from industrial grade steel



GCD83075 OLP



Hose Reel Carts & Trailers

See page 27



NEW!

Reel Covers

See page 41



Roller Guide Assemblies

See page 43 for additional Series 30000 accessories



Interactive Reel Catalog

Visit reelcraft.com/catalog for complete product specifications, parts, and accessories.



Pivot Bases & Swing Brackets

See page 43



Hose Assemblies & Bumper Stops

See page 40

Model with hose & bumper	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		Pressure		GH(M) Hose Outlet	GH(F) Reel Inlet	Inlet Hose (included)	Size Index Page	Size Index #
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in	in			
Spring Driven Water Hose Reels Maximum temperature 150 °F (65 °C)															
7850 OLPSW57**	51	24	1/2	13	.810	21	50	15	300	21	3/4	1/2 NPT	-----	12	----
GC7850 OLP***	47	21	1/2	13	.750	19	50	15	300*	21	3/4	3/4	S601025-6	12	----
GC7535 OLP	53	24	5/8	16	1.00	26	35	11	200*	18	3/4	3/4	600830-10	12	----
GCD85100 OLP	101	46	5/8	16	1.00	26	100	31	250*	18	3/4	3/4	600830-10	14	3
GC7925 OLP	53	25	3/4	19	1.075	27	25	8	250*	18	3/4	3/4	600830-10	12	----
GC83050 OLP	89	41	3/4	19	1.075	27	50	15	250*	18	3/4	3/4	600830-10	14	1
GCD83075 OLP	102	46	3/4	19	1.075	27	75	23	250*	18	3/4	3/4	600830-10	14	2
GCD84050 OLP	103	47	1	25	1.375	35	50	15	250*	18	1	1	S600982-10	14	3

*Garden hose end fitting supplied on the outlet hose is rated to 150 PSI. **Does not include inlet hose; 50 ft. hose assembly is yellow and does not include ball valve. ***Does not include ball valve.

Model (does not include outlet hose)	Shipping Weight		Hose I.D.		Hose O.D.		Hose Length		**Max Pressure	(M) Reel Outlet	(F) Reel Inlet	Inlet Hose (included)	Dimensions - Page 26						
	lbs	kg	in	mm	in	mm	ft	m	psi	bar	in		in	D		E		F	
Hand Crank Water Hose Reels Maximum temperature 150 °F (65 °C)																			
GCCA33112 L	47	21	3/4	19	1.075	27	100	31	300	21	3/4 GH	3/4 NPT	600830-10	15 ³ / ₄	400	25 ³ / ₄	654	12	305
GCCA33118 L	52	24	3/4	19	1.075	27	175	54	300	21	3/4 GH	3/4 NPT	600830-10	21 ³ / ₄	552	31 ³ / ₄	806	18	457
GCCB37118 L	55	25	1	25	1.375	35	100	31	300	21	1 NPT	1 NH	S600982-10	21 ³ / ₄	552	31 ³ / ₄	806	18	457