


Reotemp RTD Assembly



Part#: B-1T-PX1252.5X

Description:

RTD Assembly, with Cast Aluminum Head, Spring-loaded 316SS Bushing, 1/2" NPT, 3-wire Single (Standard), Std temp RTD (Pt/385/ Class B (Standard), 100 ohm), 1/4" dia. X 2.5 in. long, 316SS stem

Head Data:

Description: Cast Aluminum
Material: Cast Aluminum
Color: Gray
Conduit Conn. "P": 3/4"NPT Conduit
NEMA/IP rating: Nema 4X/IP68

In- Head:

Ceramic Terminal Block

Power In:

Signal Out:

Protocol:

Approvals:

Note:

Process Connection:

Spring-loaded 316SS Bushing, 1/2" NPT
 (Thermowell Required. Stem retracts nominal 1/2" max in well.)

Stem Data:

Stem Length "L": 2.5 in.
Stem "D" (in.): 1/4"
Stem Jacket Material: 316SS
Min. Recommended Immersion (without thermowell): 2.5"

Sensor Data:

Sensor: RTD
Resistance @ 0°C: 100 ohm
Tolerance Class (IEC 60751): B
Sensors: Single
Temperature Range: Std. Range: -328F to 400F (-200C to 204C)

Revision Status:	Data generated on: 1/24/2020
Latest Revision:	x3
Revision Date:	12/1/2015
Description:	Stm length

*Revision date applies to all possible data: Individual drawings may not be affected. To obtain current revision, re-generate drawing at www.reotemp.com

Dimensions are in inches.

Consult factory for critical dimensions.

Copyright © 2013
 REOTEMP Instruments

REOTEMP Instrument Corporation
REOTEMP
 INSTRUMENTS

10656 Roselle Street
 San Diego, CA 92121 USA
 Phone: (858) 784-0710
 Fax: (858) 784-0720

DRAWN BY: JR
SIZE: B
CAGE CODE: 24793

THIS DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF REOTEMP INSTRUMENT CORP., AND ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS DEPICTED HEREIN WITHOUT WRITTEN PERMISSION FROM REOTEMP INSTRUMENT CORP.

SCALE: NTS
SHEET: 1 OF 1

Made in U.S.A.