
Reotemp RTD Assembly



Part#: E-1T-PX1252.5X

Description:

RTD Assembly, with Explosion Proof Aluminum (FM, FMC, CSA) Head, Spring-loaded 316SS Bushing, 1/2" NPT, 3-wire Single (Standard), Std temp RTD (Pt/385/ Class B (Standard), 100 ohm), 1/4" dia. X 2.5 in. long, 316SS stem

Head Data:			
Description:	Explosion Proof Aluminum (FM, FMC, CSA)		
Material:	Cast Aluminum		
Color:	Gray		
Conduit Conn."P":	3/4"NPT Conduit		
NEMA/IP rating:	Nema 4X/IP68		
Hazardous Area	Class I, Div 1, Grps B,C,D Class II, Div 1, Grps E,F,G		
Approval:			
Ву:	FM, FMC		
In- Head:	Ceramic Terminal Block		
Power In:			
Signal Out:			
Protocol:			
Approvals:			
Note:			
Process Connection	ı: Spring-lo	paded 316SS Bushing, 1/2" NPT	
	(Thermowell Required. Stem retracts nominal 1/2"		
		max in well.)	
Stem Data:			
Stem Length "L":		2.5 in.	
Stem "D" (in.):		1/4"	
Stem Jacket Material:		316SS	
Min. Recommended Immersion		2.5"	
(without thermowell):		2.0	

Sensor Data:	Sensor:	RTD	
Resistance @ 0°C:		100 ohm	
Tolerance Class (IEC 60751):		В	
# Sensors:		Single	
Temperature Range:		Std. Range: -328F to 400F (-200C to	
		204C)	

Revision Status: Data generated on: 1/24/2020 Latest Revision: x3 Revision Date: 12/1/2015 Description: Stm length

*Revision date applies to all possible data: Individual drawings may not be affected. To obtain current revision, re-generate drawing at www.reotemp.com

Dimensions are in inches.

Copyright © 2013

REOTEMP Instruments

Consult factory for critical dimensions.

Made in U.S.A.

REOTEMP Instrument Corporation
REOTEMP 10656 R
San Diego, C
Phone: (8)
Fax: (85

10656 Roselle Street San Diego, CA 92121 USA Phone: (858) 784-0710 Fax: (858) 784-0720 JR
SIZE:
B
CAGE CODE:
24793
SCALE:
NTS
SHEET:
1 OF 1

THIS DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF REOTEMP INSTRUMENT CORP., AND ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS DEPICTED HEREIN WITHOUT WRITTEN PERMISSION FROM REOTEMP INSTRUMENT CORP.